
DV16D1



Features

- Real-time Full D1 Recording and playback (NTSC480 fps @ 16CH)
- Various Output (1 HDMI, 1 VGA1 CVBS, 16 Channel Loop-Back, 4 SPOT)
- 16 Channel Audio Recording
- Instant and Convenient Backup via USB Flash Drive, Network or DVD-RW
- Free Private DDNS & Public DDNS
- e-mail Event Notification over IP change, Motion detection, Sensor in, S.M.A.R.T
- Digital Zoom in Live, Playback, Network, and Backup viewer
- Full Network Dual Streaming Control
- Variety of Ways Network Access via Network Client Software, Web-Viewer, CMS, and Mobile Viewer

DIMENSIONS



DV04HD

MODEL	DV16D1
Video Compression	H.264
Video Input	16 Composite (NTSC/PAL Auto Detection)
Video Output	1 HDMI (Max. 1920x1080p60 and Various Resolution) 1 VGA (Max. 1920x1080p60 and Various Resolution) 1 CVBS (704x480 / 704x576) 4 SPOT (704x480 / 704x576)
Audia Carranasia	
Audio Compression	G.711
Audio Input	4 RCA
Audio Output	1 RCA, 1 HDMI
Sensor Input	16 TTL, NC/NO Selectable
Alarm Output	4 Relay Out by Sensor, Motion and Video Loss
POS	1 RS-232C (DSUB 9)
PTZ	1 RS-485
Keyboard Controller	1 RS-485
USB	2 USB 2.0 (1 Front Panel and 1 Rear Panel)
Network	1 Gigabit Ethernet (RJ-45), Auto MDI/MDIX
Multiple Operation	PentaPlex (Live/Recording/Playback/Backup/Network)
Live Zoom	Digital Zoom (Zoom-in of specific area)
Motion Detection	Yes
Recording Resolution	NTSC(704x480, 704x240, 352x240) or PAL(704x576, 704x288, 352x288) per Channel
Recording Quality	5 Levels
Recording Mode	Continuous, Schedule, Motion, Sensor, Manual
Pre-Recording	Min. 15 seconds and Max. 20 minutes
Post-Recording	Min. 10 seconds and Max. 60 seconds
Watermarking	Yes
Search Mode	Timeline, Event, Archive, Log and First/Last/Specific Time
Playback Zoom	Digital Zoom (Zoom-in of specific area)
Playback Speed	x0.25, x0.5, x2, x4, x8, x16, x32
Instant Playback	Yes
Backup File Format	JPEG(Snap Shot), Proprietary Format(Video Clip)
	USB Stick/HDD(using by USB Port)/DVD
Backup Media	
Huge Backup	Yes
Backup Player	Built-in Player for PC
Internal Storage	4 SATA HDDs(without ODD)
External Storage	2 e-SATA (up to 16TB)
S.M.A.R.T	HDD Error Check and Reporting using by Alarm and e-Mail
Filesystem	Self-developed, Reliable and Stable Filesystem
User Interface	Graphic User Interface, Mouse, IR Remote Controller and Keypad
Dual Streaming	Resolution, Frame Rate and Quality Control per Channel
PC Client	Live, Search/Playback, Backup and PTZF
Web Client	Live, Search/Playback, Backup and PTZF
Remote Setup	Yes
Remote Upgrade	Yes
3G Mobile	Yes (iPhone, Android, Blackberry)
DST (Daylight Saving Time)	Yes
Multiple Language	Yes
NTP	Yes
DDNS	Yes
Protocols	RTP, RTSP, RTCP, HTTP, DDNS, NTP, SMTP, DHCP
Operational Condition	5°C~40°C (41°F~104°F), Humidity 20~80%
Power	AC 100~120V/200~240V, 50/60Hz, 280W
Net Weight (Gross Weight)	6.8 kg (9.0 kg) / 15.0 lbs (19.8 lbs)
Unit Dimension (W x D x H)	432mm x 430mm x 98mm (17.00" x 16.92 " x 38.58")
(x B x 11)	CE, FCC, KCC