



HIGH RESOLUTION, BOX CAMERA, ELECTRONIC DAY AND NIGHT, TRUE DAY AND NIGHT

Commercial, Residential, Banking, Transportation,
Education, Law Enforcement, Retail and C-Store



C232D/Digital Color Camera, High Resolution, Day and Night

C232T/Digital Color Camera, High Resolution, True Day and Night

The C232D and C232T are high performance, high resolution, Day and Night cameras which perform very well in extreme low light environments. Providing the best color images under both normal and low light conditions, these two models offer innovative features in a sleek attractive design.

Additional features include: Simple OSD, True Day and Night, Motion Detection, Programmable Privacy Zones, AGC, AWB, Dual Voltage, and a 5 Year Warranty.






www.digital-watchdog.com

Electronic

1/3" Sony Super II HAD CCD
 540 TV Line
 On-Screen Menu Programming
 Low Power Consumption
 Auto Sensing 24 VAC/12 VDC
 Ultra Low-Light Sensitivity
 TDN (True Day and Night/IR Cut Filter) (C232T)
 Electronic Day and Night Mode (C232D)
 AGC (Auto Gain Control)
 BLC (Back Light Compensation)
 AWB (Auto White Balance)
 Mirror Image Control
 Programmable Privacy Zone and Motion Detection
 Sharpness Control
 5 Year Warranty

Mechanical

C or CS Mount Lens



SPECIFICATIONS: C232T (True Day and Night)/C232D (Day and Night)

Camera TYPE	Color/BW	Box Camera
Image	Device	1/3" Super HAD II CCD
	Pixels-Total	811 (H) x 508 (V)
	Pixels-Effective	768 (H) x 494 (V)
Scanning	System	525 line, 2:1 Interlace
	Horizontal Frequency Internal Mode	15,734Hz
	Vertical Frequency Internal Mode	59.94Hz
Min. Scene Illumination	F1.2 [30 IRE]	0.1 Lux [at TDN: 0.01Lux]
Functions	BLC	ON/OFF (Area Setting)
	AGC	ON/OFF (Gain Adjust)
	AWB	ATW/AWB/Fixed/Manual
	Mirror	ON/OFF
	Motion Detection	ON/OFF (Area/Sensitivity/Trace ON/OFF)
	Privacy Zone	4 Programmable Zone/Size
Lens	C/CS	DC Varifocal Lens [Option]
Resolution	Horizontal	540 TV Lines [at TDN (B/W) :570 TV Lines]
Video Output	VBS 1.0Vp-p	VBS 1.0Vp-p (75 Load)
S/N Ratio	S/N Ratio	48dB
OSD	OSD	YES
Environmental Conditions	Operating Temperature	-10°~+55° (14°~131°)
	Humidity	Less than 90%
Power	Power Requirement	12VDC/24VAC (60Hz)
	Power Consumption	12VDC: .[130mA]/24VAC:[.110mA]
Physical Specifications	Dimensions (O x H)	62.0 x 58.8 x 131.8mm
	Weight	0.7 lbs
Certifications	CE, FCC, RoHS	Certified



5436 W. Crenshaw Street • Tampa, FL 33634
 Toll Free: 866.446.3595 • Fax: 813.888.9262