

EAX® EXIT ALARMS

EAX-3500

Timed Bypass Exit Alarm and Rechargeable Battery

The Detex EAX-3500 is designed for applications requiring a hard-wired, timed-bypass alarm with rechargeable backup battery. The 100dB alarm will sound when someone attempts an unauthorized exit. The EAX-3500 can be temporarily bypassed for deliveries and trash removal, but reminds manager to close and secure the door.

Shown with cylinder (mortise cylinder sold separately)



Benefits

- Allows manager to temporarily bypass the alarm, but does not allow the alarm to be turned off
- Minimizing door prop time reduces exposure to theft and threat of robbery
- Alarm demands attention even in noisy environments
- Reminds manager to close and secure the door, minimizing door prop time
- Simple, on-the-cover instructions make operation easy
- Tamper-resistant housing and circuits prevent dishonest employees from defeating alarm
- Minimizing door prop time saves energy costs
- LEDs illustrate armed status and bypass time, allowing quick easy reference
- Mortise cylinder sold separately, helping to maintain key control

Features

- Hard-wired low voltage power with rechargeable battery insures uninterrupted secure power feed
- 100dB alarm, powered by 12 to 24 VAC and rechargeable backup battery (included)
- Accepts 5, 6 or 7-pin standard and interchangeable core mortise cylinders with a standard Yale cam
- Maximum allowable bypass time can be factory set or field-adjusted to 5, 10, 20 or 40 minutes
- Low battery alert
- Patented cam assembly automatically adjusts for different size/length cylinders without the use of additional spacers or cylinder collars
- Bypass time is easily set using two simple slide jumpers, located inside secured enclosure
- Rechargeable backup battery provides 72-hours of operation
- Resetting the alarm can only be accomplished with a control key
- Timed bypass allows alarm to remain bypassed for allotted minutes, automatically rearming upon door closing

Mechanical Options

- EAX-3500 includes surface mount timed-bypass alarm, rechargeable battery (mortise cylinder sold separately)
- EAX-3500SK includes surface mount timed-bypass alarm, rechargeable battery, surface magnetic switch and plug-in 24VAC transformer (mortise cylinder sold separately)
- EAX-3500FK includes flush mount timed-bypass alarm, rechargeable battery, flush magnetic switch and plug-in 24VAC transformer (mortise cylinder sold separately)

Accessories

- IC7 - Interchangeable core mortise cylinder
- MC65 - Mortise cylinder
- Optional Cylinder Nut Wrench P/N: 103779



Technical Information


- Machine and Self Drilling Screws (Std.)
- Amp Draw - .083 Amps @ 24 VDC (Alarmed)
- .110 Amps @ 24 VDC (Door Prop)

Dimensions


Back - Side View

Front View

Cover - Side View



Riser Diagram



Listings and Approvals



“UL Listed”



ANSI/BHMA Certified
A156.29

Detex Limited Warranty

3 Year Limited Manufacturers
Warranty



Detex Corporation
302 Detex Drive
New Braunfels, Texas 78130-3045 USA
PH. (830) 629-2900
(800) 729-3839
FAX (830) 620-6711
(800) 653-3839
<http://www.detex.com>
USA Sales:
marketing@detex.com
International Sales:
export@detex.com