

ED560


560 TVL Outdoor Vandal Color Dome with True Day/Night



Features

- 1/3" Sony Super HAD color CCD
- 560 TVL of horizontal resolution
- Advanced 16-bit Digital Signal Processor (DSP) for excellent picture quality
- Capture clear images in almost complete darkness with low 0.002 Lux (SENS-UP technology)
- True Day/Night function with removable IR cut filter
- Built-in Dynamic Noise Reduction (DNR) for noise reduction and a 70% saving of disk storage
- 3-axis rotation for viewing flexibility
- Easy installation for wall or ceiling mount
- OSD setting menu
- Support Motion Detection function
- Support Privacy function
- Vandal resistant to withstand intentional destruction
- Weatherproof IP66 rated to endure all weather conditions

Dimensions



Specifications

Pickup Device	1/3" Sony Super HAD CCD
Video Format	NTSC or PAL
Scanning System	NTSC: 525 TVL, 60 fields/sec. PAL: 625 TVL, 50 fields/sec.
Picture Elements	768 x 494 (NTSC) / 752 x 582 (PAL)
Horizontal Resolution	560 TVL
Sensitivity	0.002 Lux (SENS-UP 128X), 0.25 Lux/ F=1.2
S/N Ratio	Over 50 dB (AGC off)
Electronic Shutter	1/50(1/60) ~ 1/100,000
Lens Type	Vari-foca f=2.9~10mm, f=9~22mm
Backlight Comp.	Off/Low/Middle/High Adjustable
Auto Gain Control	Off/Low/Middle/High Adjustable
Auto White Balance	ATW(2500 oK ~8300 oK)/AWC/Manual
Gamma Correction	0.45
True Day/Night	Yes
Flickerless	Yes
Video Output	2 BNC 1.0Vp-p, 75ohm Additional testing video output: 1.0Vp-p, 75ohm
Sync. Mode	Line Lock/Internal sync.
H-Mirror	Yes
OSD Menu	Yes
Vandal Resistant	Yes
Power Source	12VDC/24VAC
Power Consumption	24VAC: 5W max., 12VDC: 3.5W max.
Dimension (W x H)	123 x 107.8 mm / 4.8" x 4.2"
Weight	0.74 kg / 1.6 lbs
Operating Temp.	-10°C ~ 50°C / 14°F ~ 122°F (20% ~ 80% Humidity)
Weatherproof	IP66 rated

Ordering Information*

- **ED560D/MV3:** f=2.9~10mm, 12VDC/24VAC, Day/Night, Outdoor, Dome Camera
- **ED560D/MV2:** f=9~22mm, 12VDC/24VAC, Day/Night, Outdoor, Dome Camera
- **ED560T/MV3:** f=2.9~10mm, 12VDC/24VAC, True Day/Night, Outdoor, Dome Camera
- **ED560T/MV2:** f=9~22mm, 12VDC/24VAC, True Day/Night, Outdoor, Dome Camera

*Models vary in different countries. Please visit EverFocus regional websites for detailed ordering information.