



Starter Kit

Expansion Kits

Kantech Access Control Starter and Expansion Kits offer a comprehensive solution for growing businesses that are seeking an easy-to-use and highly reliable access control system.

The all-inclusive Starter Kit provides everything needed to create a complete access control system. From the powerful EntraPass software and KT-300 door controller to all of the peripherals in between, the Starter Kit makes sure nothing is left to chance.

Similarly, the Expansion Kit includes everything required to expand an existing system. In two-door increments, the Expansion Kit keeps up with even the fastest growing business.

IP Link

The IP Link uses 128-bit AES encryption to communicate with EntraPass, which ensures communication when used over the Internet. IP Link manages polling of door controllers and communicates with EntraPass Gateway only when an event has occurred. This significantly reduces the amount of bandwidth required to manage your access control system over a network. Up to 512 IP Links can be supported per EntraPass Gateway, and IP Link supports up to 32 door controllers.

The Expansion Kit with IP Link makes it easy and affordable to manage your Kantech access control system over a network. The IP Link leverages Kantech's robust portfolio of KT-controllers to offer a powerful security solution for any size application.

The Expansion Kit with Modem is ideal for applications where an "always-on" connection is not required, or where a network is inexistent.

Access Control Starter and Expansion Kits

Features That Make a Difference:

- Everything you need to install or expand a complete access control system
- Easy to install and easy to use
- Expand your access control system in two-door increments using the Access Control Expansion Kit
- Compatible with EntraPass Special Edition, Corporate Edition, and Global Edition
- Expansion Kit with IP Link (KT-IP) provides communication over the network
- Expansion Kit with IP Link (KT-IP) is compatible with EntraPass Special, Corporate, and Global Editions (Global Edition with Corporate Gateway only)¹
- Expansion Kit with modem enables EntraPass to connect to remote sites (RS-232 from remote modem to controller)

EntraPass Special Edition Software

EntraPass Special Edition software, included in the Starter Kit, is an expandable single workstation solution that is easy to use. Please see the EntraPass Special Edition data sheet for more information.

KT-300 Door Controller

KT-300 is a powerful and scalable door controller that manages two doors or can be easily linked to a network controlling thousands of doors. Additionally, KT-300 supports expansion modules to add inputs, outputs, and an LCD for time and attendance functions.

The P225XSF ioProx readers are attractive, compact, and vandal resistant. Each reader is also encapsulated in epoxy potting which protects them from the elements. The innovative 'snap-and-lock' terminal blocks allow for easy wiring saving time and money. The eXtended Secure Format (XSF) increases security and protects against card duplication. Each reader is outfitted with an integrated piezo buzzer and bicolor LED and has a read range of up to 16.5 cm (6.5 in).

ioProx Keytags

The Starter Kit contains five P40KEY keytags that are small enough to fit on a key chain and are resistant to cracking and breaking.

USB-485 Converter

The USB-485 protocol converter converts USB to RS-485 and extends communication up to 1,200 m (4,000 ft). The converter uses an unshielded and twisted communication cable and is powered by a USB port.

(1) IP Link is supported by v4.0 or greater.

EntraPass Special Edition

Cards	Unlimited
Number of Cards in Standalone Mode	8,000
Card Families or Site Codes	Unlimited
Number of Sites	Up to 64 (max. 64 controllers)
Door Controllers Per Site	32
Monitored Points (Input)	512 per site
Card User Access Levels	250 per site

KT-300 Door Controller

Input Power	16 VAC, 40 VA, Class 2 transformer
Battery Backup	One 12V battery 12V/7Ah, supervised, provides operation for up to 12 hours
Dimensions (H x W x D)	29.9 x 28.8 x 7.7 cm (11.75 x 11.375 x 3 in)
Operating Temperatures	From 2° to 40°C (35° to 110°F)
Reader Types	Wiegand, proximity, bar code, magnetic, integrated keypad, and others
Monitored Points (Inputs)	Eight monitored points, NO/NC, with or without end-of-line resistors (expandable to 16)
Door Strike Power	12 VDC, 250 mA each, supervised
Auxiliary Power Output	12 VDC @ 125 mA max., protected and supervised

IP Link

Communication Ports	RJ-45 Ethernet 10/100Base-T and RS-232
Communication Speed	Up to 115,200 baud for serial communication
Flash ROM	2 MB
RAM	8 MB
Compatibility	KT-100, KT-200 and KT-300 door controllers
Maximum Unit	Up to 512 IP Links per Corporate Gateway Up to 64 IP Links per Special Edition
Operating Temperature	0° to 49°C (32° to 122°F)
Humidity	0 to 85% non-condensing, indoor use only
DC Power Input	12 VDC
Input Current	Max: 175 mA, Typical: 125 mA

P225XSF ioProx Readers

Typical Read Range	Up to 16.5 cm (6.5 in)
Input Voltage	4.5 to 14 VDC
Current DC Maximum	45 mA
Dimensions (H x W x D)	114.3 x 44.5 x 21.3 mm (4.5 x 1.75 x 0.84 in)
Weight	90.7 g (3.2 oz)
Color	Black
Transmit Frequency	125 KHz
Operating Temperature	-35° to 65°C (-30° to 150°F)
Format	XSF

Ordering Information

SK-SE302²

Starter Kit Includes: EntraPass Special Edition software CD-ROM, KT-300/128K controller (1), ioProx P225XSF readers (2), USB-485 converter (1), TR1640P/UL transformer (1), 12V/7Ah battery (1), KT-RM1 relay (2), and ioProx P40KEY keytags (5). (US only)

EK-302²

Two-Door Expansion Kit Includes: KT-300/128K controller (1), ioProx P225XSF readers (2), TR1640P/UL transformer (1), 12V/7Ah battery (1), and KT-RM1 relay (2). (US only)

EK-IP300³

Two-Door Expansion Kit with IP Link Includes: KT-300/128K controller (1), VC-485 converter (1), TR1640P/UL transformer (1), 12V/7Ah battery (1), KT-RM1 relay (2), and KT-IP communication device (1). (US only)

EK-IP302³

Two-Door Expansion Kit with IP Link Includes: KT-300/128K controller (1), ioProx P225XSF readers (2), VC-485 converter (1), TR1640P/UL transformer (1), 12V/7Ah battery (1), KT-RM1 relay (2), and KT-IP communication device (1). (US only)

EK-DU300³

Two-Door Expansion Kit with Modem Includes: KT-300/128K controller (1), TR1640P/UL transformer (1), 12V/7Ah battery (1), KT-RM1 relay (2), and DU-MODEM-RS modem (1). (US only)

EK-DU302³

Two-Door Expansion Kit with Modem Includes: KT-300/128K controller (1), ioProx P225XSF readers (2), TR1640P/UL transformer (1), 12V/7Ah battery (1), KT-RM1 relay (2), and DU-MODEM-RS modem (1). (US only)

(2) For Canadian customers, please add suffix "CDN" to part number to receive the CSA-compliant transformer (SK-SE302CDN or EK-302CDN).

(3) For Canadian customers, please add suffix "-CDN" to the product number to receive the CSA-compliant transformer (EK-IP300-CDN or EK-IP302-CDN or EK-DU300-CDN or EK-DU302-CDN).

The trademarks, logos, and service marks displayed on this document are registered in the United States [or other countries]. Any misuse of the trademarks is strictly prohibited and Tyco International Ltd. will aggressively enforce its intellectual property rights to the fullest extent of the law, including pursuit of criminal prosecution wherever necessary. All trademarks not owned by Tyco International Ltd. are the property of their respective owners, and are used with permission or allowed under applicable laws.

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

