

EN-7515C/EN-7517C EN-7519C

15", 17" or 19" Premium LCD DVR Monitor



Features

- 15", 17" or 19" LCD DVR monitor
- Active matrix TFT
- HDMI input
- BNC/S-Video/VGA
- Multi-lingual language support
- Compatible with VESA™ DDC
- 3D comb filter
- UL, CB, FCC, CE Listed
- Remote control included

Specifications

Model	EN-7515C	EN-7517C	EN-7519C
Screen Size	15"	17"	19"
Viewing Area (mm)	N/A	337x270	376x301
Pixel Type	Active Matrix TFT		
Max. Resolution	1024 x 768 @ 60Hz	1280x 1024 @ 60Hz	
Pixel Pitch	0.297x0.297 mm	0.264x0.264 mm	
Brightness	250cd/m ²	300cd/m ²	
Contrast Ratio	450:1	1000:1	
Aspect Ratio	4:3	5:4	
Viewing Angle (H/V)	130°/110°	160°/160°	
Display Color	16.2 million		16.7 million
Response Time	<12ms	< 5ms	
Video System	NTSC/PAL		
Frequency (H)	31~48 KHz	31 ~ 64 KHz	
Frequency (V)	55 ~ 75Hz		
Built-in Speakers	Yes (2Wx2)		
Gradual Volume Increase	Yes		
Video In/Out (BNC Type)	2/2		
S-Video In/Out	1/1		
VGA In (15 Pin D-Sub)	1		
DVI In	No		
Audio In/Out (RCA Type)	1		
PC Stereo In	2 set (L+R)	1 set (L+R), no output	
Filter Type	3D Comb Filter/DeInterlace		
Dimensions (w/stand)	348x289.6x134.6 mm / 13.7" x 11.4" x 5.3"	436.8x475x226 mm / 17" x 15" x 8.9"	500x515x240 mm / 20" x 20.3" x 9.4"
Net Weight	4.8 kg / 10.6 lbs	5.9 4kg / 13.1 lbs	6.6 kg / 14.6 lbs
Gross Weight	N/A	7.66 kg / 16.9 lbs	8.43 kg / 18.6 lbs
VESA Mounts Size	75x75mm (BS M4 x 10mm screw)	100x100 mm (BS M4 x 10mm screw)	
Parts/Labor	2 years/2 years		
MTBF (approx.)	50,000 hours		
Regulations	TUV-NRTL (same as UL), CB, FCC(A), CE-EMC(LVD)		
Power Consumption	< 35W	< 36W	
Power Source	AC100~240V (50/60Hz), 12VDC/3.5A	AC100~240V (50/60Hz), 12VDC / 4.12A	
Operating Temp.	10°C ~ 40°C / 50°F ~ 104°F	10°C ~ 40°C / 50°F ~ 104°F	

Ordering Information

- **EN-7515C:** 15" LCD Monitor, Active Matrix TFT, 1020x768, HDMI
- **EN-7517C:** 17" LCD monitor, Active Matrix TFT, 1280x1024, HDMI
- **EN-7519C:** 19" LCD monitor, Active Matrix TFT, 1280x1024, HDMI