

OUTDOOR EMERGENCY PHONES

0

EMERGENCY

111

ETP-400

0

ETP-400 – Single Button Emergency Phone

Description

The **ETP-400** is an outdoor-rated, ADA-compliant hands-free Emergency Phone for use in locations such as: parking facilities, college campuses, controlled access gates, medical centers and industrial parks.

Features

- Cast metal raised letter and Braille signage for ADA compliance
- Vandal resistant stainless steel faceplate and metal button
- Uses regular phone lines or PBX
- · Phone line powered: no power supply or battery back-up needed
- Circuit boards are conformally coated for water protection
- · LED indicator for hearing impaired
- Auxiliary input and outputs to integrate with CCTV, Blue Light Strobe, Scream Alert™ and other devices
- · Built-in auto-dialer can dial two numbers: if first number doesn't answer or is busy, dials second number
- Auto-answer allows security to monitor and initiate calls with Emergency Phone
- Options available that offer the ability to automatically identify attendant of location of calling phone by recorded message and digital display

Specifications

Construction: 12 gauge (2.8mm) #4 brushed stainless steel faceplate Dimensions: 9.5(241) W x 11.75(298) H in(mm)

Back Box: 6.63(168) W x 9.75(248) H x 2.5(64) D in(mm)

Weight: 8 lbs. (3.6kg)

Operating Temperature: -4°F to +149°F (-20°C to +65°C)

Mounting: Flush mounts (surface mount options available)

Communication: 2-way hands-free communication

Digit Capacity: Up to 18 digits, including pauses, for each of two phone numbers

Dialing Speed: Approximately 10 tones per second

Power Source: Phone line powered (requires 20mA at 24 v off-hook)

Connection: Parallel tip and ring connected to RJ11 connector for quick installation

Circuit Protection: Varistor lightening suppressed and full wave polarity guarded

Programming: Non-volatile EEPROM programming can be done from any telephone

No battery back up is needed

"On Time": Programmable from 1-4270 minutes in 1-minute increments

Recommended Wiring: 1 twisted-shielded pair

Compliance: CSA Certified to UL Standard 60950

Options & Accessories

Voice Location Identifier: Model ETP-400V includes the capability to record a message identifying the

location of the call. Message is recorded and duration set during programming

"TO CALL" Casting: Use Model **ETP-400C** for a button that reads TO CALL instead of **EMERGENCY**

8-Line Consolidator: Model EC-8 allows connection of up to 8 phones on one phone line while retaining ability

to call each phone individually. Can also create a closed system without need for any

phone lines

Monitoring/Diagnostic Software Package:

Talk-A-Lert®, model ETP-TAL, automatically polls each Emergency Phone, reports

incoming calls and keeps permanent records of all events

Faceplate Camera: Add "OP3" to model number to add a color pinhole camera mounted discreetly behind the

faceplate. Add "OP3BW" for a b/w camera

Copyright 2009 Talk-A-Phone Co. All rights reserved.

ETP-400 - Single Button Outdoor Emergency Phone

Dimensions

