![Talk A Phone logo - Creating Communications Solutions®]

ETP-400H-NC – Handset Emergency Phone

Description
The **ETP-400H-NC** is an outdoor-rated Emergency Phone with a handset for use in noisy areas or other locations where private conversation is desired.

Features
- Built-in auto-dialer can ring down or dial two pre-programmed numbers when CALL button is pushed: if first number doesn't answer or is busy, it dials the second number
- Vandal resistant stainless steel faceplate and metal "CALL" button
- Phone line powered: no power supply or battery back-up needed
- All circuit boards are conformally coated for water protection
- Volume control push button on the handset
- Noise cancelling microphone
- Auxiliary input and outputs to integrate with CCTV, LED Blue Light, Scream Alert and other devices
- Includes the ability to automatically and remotely poll each telephone and diagnose its health. As an option, also identify location of calling phone by recorded message and digital display

Specifications

Construction:	12 gauge (2.8mm) #4 brushed stainless steel faceplate
Dimensions:	Front Panel: 9.5(241) W x 11.75(298) H in(mm)
	Wall Opening: 6.63(168) W x 9.75(248) H x 2.5(64) D in(mm)
Handset/cord:	G-style handset resting on a metal cradle with a 15-inch lanyard armored cord
Weight:	8 lbs. (3.6kg)
Operating Temperature:	-40ºF to +149ºF (-40ºC to +65ºC)
Mounting:	Flush mount (surface mount options available)
Communication:	2-way handset communication; noise cancelling microphone
Digit Capacity:	Up to 18 digits, including pauses, for each of two phone numbers
Dialing Speed:	Approximately 10 tones per second
Power Source:	Phone line powered
Connection:	Parallel tip and ring connected to RJ11 connector for quick installation
Circuit Protection:	Varistor lightening suppressed and full wave polarity guarded
Programming:	Non-volatile EEPROM programming can be done from any telephone. Remote diagnostics of the phone are provided via ETP-TAL. No battery backup is needed
"On Time":	Programmable timeout or remote party disconnect from 1-4270 minutes in 1-minute increments
Approvals:	UL/CSA 60950, Type 3R NEMA Enclosure rated and FCC 47 CFR Part 68 Certified.

Options & Accessories

Voice Location Identifier:	Model **ETP-400HV-NC** includes the capability to record a message identifying the location of the call.
8-Line Consolidator:	Model **EC-8** allows connection of up to 8 phones on one phone line while retaining ability to call each phone individually. Can also create a closed system without need for any phone lines.
Monitoring/Diagnostic Software Package:	Talk-A-Lert®, model **ETP-TAL,** automatically polls each Emergency Phone, reports incoming calls and keeps permanent records of all events

Talk-A-Phone Co. • 7530 North Natchez Avenue • Niles, Illinois 60714-3804   Rev. 5/10/11
Phone 773.539.1100 • Fax 773.539.1241 • info@talkaphone.com • www.talkaphone.com
All prices and specifications are subject to change without notice. Talk-A-Phone,
Talk-A-Lert, Scream Alert, WEBS and WEBS Contact are registered trademarks of Talk-A-Phone Co.