



FB-1108

Wall or ceiling indoor housing

Why double stock wall and ceiling housings when this versatile one can be used for both?

This is cost-cutting stock management ! Use this tamperproof housing on any wall or ceiling and in each case you will be able to adjust the camera with a 35° angle. The innovation lies in the way the cover is hinged. This new design allows the housing to be attached directly against a lateral wall or in a corner without preventing the cover to open freely and totally. It also allows the use of rigid pipes. The cover is tamperproof and locked by a security T-bolt with retainer. The window comes with a 3/16" polycarbonate. Requires only 4 screws for a fast and easy installation on any surface. For longer camera sizes see our **FB-1110** or **FB-11S1** housings.

Fabrication :

Body : All aluminum, gauge 11, alloy # 3105H14
 Window : 3/16" clear polycarbonate
 Cover : Hinged, tamperproof, locked by a security T-bolt with retainer
 Finish : White polyurethane coating
 Weight : 3 lb (1.37 kg)

External Dimensions :

Height : 5.5" (143 mm)
 Width : 4.75" (120 mm)
 Length : 11.375" (288 mm)

Internal dimensions:

Height: 3.0" (76 mm)
 Width: 3.25" (83 mm)
 Length: 8.0" (203 mm)
 Camera : 8.0" (203 m) max. length

