

## FC-4001

MultiCoder® Universal Analog & Digital Format Video Transcoder & TBC













The FC-4001 is a high-performance broadcast quality, universal video transcoder for analog and digital video signals. It converts a composite video, s-Video (Y/C), component video (RGB/S) or SDI video signal to either component or composite and s-Video (Y/C) video signals and to two SDI video signals.

## **FEATURES**

- Bandwidth −0.5dB to 5MHz.
- Decoding Options Based on Signal Standard Decodes 525-line signals to NTSC 3.58 or NTSC 4.43 and 625 lines to PAL-B/M/N & SECAM.
- Looping Analog Sync Input.
- Freeze Frame.
- Control Options Front panel, RS-232.
- Selectable Sync Signal Termination.
- Built-in Time Base Corrector Stabilizes sync in video sources.
- Timing Controls SCH phase & sync phase.
- Front Panel Lockout.
- Worldwide Power Supply 100-240V AC.
- Standard 19" Rack Mount Size 1U. Rack "ears" included.

## FC-4001

## **TECHNICAL SPECIFICATIONS**

INPUTS: 1 composite video: 1 Vpp/75 $\Omega$  on a BNC connector; 1 Y/C: 1 Vpp/75 $\Omega$  (Y), 0.3Vpp/75 $\Omega$  (C) on a 4-pin

connector; 1 component: Y/R-Y/B-Y (1Vpp/0.7Vpp/0.7Vpp)/75 $\Omega$  (or RGB/S) on BNC connectors; 1 SDI: SMPTE-259M, ITU-R BT.601 on a BNC connector; 1 SYNC (genlock): looped 75 $\Omega$ /Hi-Z on

BNC connectors.

OUTPUTS: 1 composite video on a BNC connector 1 Vpp/75Ω; 1 Y/C video on 2 BNC connectors: Y 1 Vpp/75Ω,

and C  $0.3\text{Vpp/}75\Omega$ ; 1 component or RGB/S video on BNC connectors  $1\text{Vpp/}0.7\text{Vpp/}0.7\text{Vpp/}75\Omega$ ; 1

SYNC on a BNC connector; 2 SDI: SMPTE-259M, ITU-R BT.601 on BNC connectors.

VIDEO PAL-B/D/G/H/I/M/N, NTSC-3.58/4.43, SECAM.

STANDARDS:

DIGITAL 10 bits.

RESOLUTION:

BANDWIDTH: -0.5dB to 5MHz.

DIFF. GAIN: 1%.
DIFF. PHASE: 1Deg.
K-FACTOR: 1%.
S/N RATIO: 63dB.
LUMA NON- 1%.

LINEARITY:

CHROMA/LUMA 1ns.

DELAY:

CONTROLS: Front-panel and RS-232; SCH phase, SYNC phase, H shift, freeze, panel lock.

POWER SOURCE: 230V AC, 50/60Hz (115V AC, USA), 14VA.

DIMENSIONS: 19" x 7" x 1U W, D, H, rack mountable.

WEIGHT: 2.6kg (5.7lbs) approx.

ACCESSORIES: Power cord, null-modem adapter, rack "ears".

