



## Product Description


The KBC FTL series is a fully-ruggedized 10/100 Ethernet media converter. It supports transmission of an Ethernet channel over either one or two, multimode or singlemode optical fibers. Full duplex operation enables distances in excess of 50km on singlemode fiber. The plug-and-play design ensures ease of installation with no electrical or optical adjustment needed. LED indicators are provided to show the operational status of the unit clearly. The series is available in compact, DIN rail or 3U chassis card configurations.



## Product Features

- Wide operational temperature range
- 100BASE-FX on fiber port
- Ultra-compact footprint
- 10/100 auto-sensing
- MDI / MDIX
- Multimode and singlemode interfaces
- Single and dual fiber
- Up to 50km on singlemode fiber

## Typical System Configuration



## Specifications

### Standards

IEEE Standard

### Data

Data Formats  
Two Way Channels  
Data Rate

### Optical

Wavelength  
Fiber  
Number of Fibers

### Power

Power Input  
Power Supply for Compact<sup>(1)</sup>

Chassis Card

IEEE 802.3 10BASE-T  
IEEE 802.3u 100BASE-TX  
& 100BASE-FX  
IEEE 802.3x Full Duplex

Ethernet  
1  
10 / 100 Mbps auto-sensing  
Half & full duplex

1310nm / 1550nm  
Multimode or singlemode  
1 or 2

12-24 Vac/dc @ 200mA  
Input: 100 ~ 240 Vac  
Output: +12 Vdc  
UL and cUL listed PSU  
Supplied from FR3 PSU

### Environmental

Operating Temperature  
Storage Temperature  
Operating Humidity  
Mean Time Between Failure (MTBF)

-40° ~ +74° C / -40° ~ +165° F  
-40° ~ +74° C / -40° ~ +165° F  
0 to 95% non-condensing  
>100,000 Hours

### Mechanical

Dimensions (Compact W x H x D)

70mm x 58mm x 28mm  
(2.8" x 2.3" x 1.1")

Number of 3U Chassis Card Slots<sup>(2)</sup>

1

### Connectors


10/100 Electrical  
Fiber

1 x RJ45  
ST, SC or FC  
(ST fitted as standard)  
2-way screw block terminal

Power<sup>(3)</sup>

Compact & DIN Rail

## Part Number Configurator



## Optical Budget

Part Code	Fiber Type	No.	Optical Budget			Wavelength nm	Approximate Transmission Distance <sup>(4)</sup>
			50µm	62.5µm	9µm		
FTL1-M2*	Multimode	2	8dB	12dB		1310	0-4km
FTL1-S2*	Singlemode	2			20dB	1310	0-30km
FTL1-S1*	Singlemode	1			20dB	1310/1550nm	0-30km
FTL1-S2*-**D	Singlemode	2			20dB	1310	0-50km
FTL1-S1*-**D	Singlemode	1			20dB	1310/1550nm	0-50km

Transmission distances up to 120km are available please contact KBC Networks for details. All KBC Networks optical transmitters are LASER based.

1. Please select the power plug from US Standard, Euro 2 Circular or UK 3 Pin square when placing order.

2. Supports maximum of up to 14 single slot cards in each 3U Chassis.

3. Power lines are crimped and fitted to screw block connector in factory.

4. Transmission distance is limited by optical loss of the fiber and loss introduced by connectors, splices and patch panels. Fiber bandwidth also limits the transmission distance.

Due to ongoing technological improvements, product specifications are subject to change without notice. KBC is not liable for any errors, omissions or changes of any description of the goods contained herein. This information is for the sole purpose of identifying the products, and KBC makes no warranty that the products conform to any description contained herein. Do not rely solely on any representations, statements, or assertions concerning these Products contained herein.