

## GV-IP CAM 1.3M VANDAL PROOF DOME COLOR



- 1.3 megapixel SONY progressive scan CCD
- Dual streaming support MJPEG and MPEG4
- Two way audio
- Digital I/O: 1 IN, 1 OUT
- Support both 12V DC and PoE
- Video Motion Detection reduces bandwidth and storage
- 3GPP/ISMA mobile application
- Privacy Mask
- Visual Automation
- 16 languages on web interface


Providing detail not seen on conventional surveillance cameras, the GV-IP Camera 1.3M features a 1.3 megapixel CCD that delivers superb video image quality. Through the use of progressive scan CCD sensor, the GV-IP Camera 1.3M is able to reproduce ultra smooth video images of fast moving objects without any pixilated edges. With high definition up to 1280 x 960 and up to 4 times higher resolution than conventional VGA/ D1 cameras, the GV-IP Camera 1.3M allows users to monitor critical areas with greater detail than ever. Moreover, with simultaneous/dual video stream and support for compliant Power-over-Ethernet (PoE) which simplifies the cabling. It allows users to view both MJPEG images and MPEG-4 videos with improved efficiency while conserving valuable bandwidth.

In providing our customers with a more complete, cost-effective IP surveillance solution, our GV-IP Camera 1.3M can seamlessly integrate with our GV-NVR software system that comes with advanced monitoring and various other video management features. When connected with the GV-IP Camera 1.3M, Special web interface support functions such as privacy mask, visual automation, picture-in-picture (PiP) view and picture-and-picture (PnP) view are also made available for facilitating detail monitoring.




Progressive scan CCD captures the entire scene of a moving object at the same time. Even and odd fields are scanned simultaneously. It reproduces smooth video quality without pixilated edges.



It provides up to 4 times higher resolution than common VGA/D1 cameras.



## SPECIFICATIONS



Camera			
Image Sensor		1/3" SONY progressive scan CCD	
Picture Elements		1280(H) x 960 (V), 1.3M CCD	
Resolution		700 TVL	
Minimum Illumination		0.1 lux at F1.2	
Shutter Speed		1.5 ~ 1/10000 sec.	
White Balance		Manual / ATW (1500 ~ 15000K)	
Lens			
Max Aperture		Wide F1.4, Tele F2.9	
Lens Focal		f = 3.3~12 mm	
Angle of View		Wide end	Diagonal 125.7° / Horizontal 89.8 °
		Tele end	Diagonal 29.9 ° / Horizontal 23.9 °
Operation			
Video Codec		MPEG4 / MJPEG	
Video Streaming		Simultaneous MPEG4 and MJPEG video stream (dual stream) Selectable single stream (MPEG4 or MJPEG)	
Resolution	MPEG4 ASP	640 x 480 (VGA), 320 x 240 (CIF), 176 x 144	
	MJPEG	120 x 960 (4 VGA), 640 x 480 (VGA), 320 x 240 (CIF), 176 x 144	
Frame Rate		30fps at 640 x 480 (VGA)	
		15fps at 1280 x 960 (4 VGA)	
Image Setting		Auto Exposure, Auto White Balance, Brightness, Contrast, Sharpness, Gamma, Mono, Reverse, Rotate 180°, Flicker-less 50/60 Hz	
Audio Codec		G.726	
Digital Input		Dry Contact	
Digital Output		Photo relay output: 40mA, 5~12VDC	
Network			
Interface		10/100 Ethernet (RJ-45)	
Protocol		HTTP, TCP, UDP, SMTP, FTP, DHCP, NTP, UPnP, DynDNS, 3GPP/ISMA RTSP	
Power over Ethernet			
PoE Standard		IEEE 802.3af Power over Ethernet / PSE	
PoE Power Supply Type		End-Span	
PoE Power Output		Per Port 48V DC, 350mA. Max. 15.4 watts	
Mechanical			
Connectors	Power	3 pins terminal block, pitch 3.5 mm	
	Ethernet	180D RJ-45 with LED	
	Audio	3 pins terminal block, pitch 2.54 mm	
	Digital I/O	4 pins terminal block, pitch 2.54 mm	
LED Indicator		Power, Link, TX	
General			
Operating Temperature		-10°C ~ 50°C / 14°F ~ 122°F	
Humidity		10% to 90% (no condensation)	
Weather Proof		IP66 standard	
Power Source		DC12V / PoE	
Power Consumption		4.2 W (max. 350mA DC 12V)	
Certificate		CE, FCC, RoHS compliant	
Dimension		ø 142 x 119mm / 5.6 x 4.7 in	
Weight		1 kg / 2.2 lbs	
Web Interface			
Installation Management		Web-based configuration	
Maintenance		Firmware upgrade through Web Browser	
Access from Web Browser		Camera live view, video recording, change video quality, zoom in/out, bandwidth control, image snapshot, digital I/O control, audio, Picture in Picture, Picture and Picture, Privacy Mask, Visual Automation	
Language		Czech / Danish / English / French / German / Hebrew / Hungarian / Italian / Japanese / Polish / Portuguese / Russian / Serbian / Simplified Chinese / Spanish / Traditional Chinese	
Applications			
Network Storage		GV-NVR, GV-MultiCam	
3G Mobile Phone		Built-in player for 3GPP/ISMA	
Live Viewing		MultiView	
CMS Server support		Control Center, CenterV2, VSM	

## OPTIONS

Optional devices can expand your GV-IP Camera's capabilities and versatility. Contact your dealer for more information.

GV-Relay V2	Working with this module, GV-IP Camera can drive the loads of relay outputs over 5V.
-------------	--------------------------------------------------------------------------------------