

Video Intercom System

GV-VP410Y Black and White Video Intercom System



Summary

The GV-VP410Y from GVI is an easy-to-use Video Intercom System. It's smart design and simple push button operation offers many benefits and conveniences, including relieving the anxiety of not knowing who is at the door, to the security-conscious business or homeowner. The system is simple to install. The built-in infrared LEDs eliminate the need for a separate illumination system for low light viewing.

To use the system a visitor presses the call button on the camera unit. A chime sounds and the visual image of the visitor appears on the inside monitor. To talk to the visitor after visual ID, simply lift the handset and talk as you would on a normal telephone call.

You also have the option of identifying visitors at the doorway without them being aware that they are being watched by simply pressing the MONITOR button.

Features

- High quality 1/3 Inch CCD outdoor camera with Infrared Illuminator LEDs for low light viewing to help identify visitors in low light situations
- 4 Inch CRT indoor monitor screen
- Smart design and simple push button operation
- Remote door lock release function
- Simple Installation
- Infrared LED built-in
- Elegant design
- Video Memory Unit (optional)
- Optional GV-VPMU Memory unit enables system to record 32 different images
- Two-way audio
- 4 Wire System

GV-VPEM

Additional Monitor for Video Door Entry System



GV-VPCR

Additional Camera Station for Video Door Entry System



GV-VPXMR

Transformer for Video Door Entry System



Specifications

Video Door Station	
CCD	Black & White 1/3" CCD
Sync System	Internal
Scanning Frequency EIA	15.75KHz(H) 60Hz(V) / CCIR: 15.62KHz(H) 560Hz(V)
Lens	Composite Video 75 Ohm 1Vp-p
External/Input Jack	Terminal Chime Bell
Illumination	0 Lux @ IR ON
Power Consumption	DC12V, 3W
Telephone Call system	4 Wire
Scanning System	525 Line (EIA), 625 Line (CCIR)
Auto Iris	Internal ALC system
Microphone	Built-in condenser type
Audio Amp	Built-in RX and TX
CCD Pixels	270,000(EIA)
Dimensions	3.78 x 5.04 x 1.81 in / 96 x 128 x 46 mm
Weight	1.39 lb / 0.63 kg
Inside Monitor/Handset Station	
Monitor	4" Black and White CRT
Scanning Frequency	15.75KHz(H) 60Hz(V) / CCIR: 15.62KHz(H) 560Hz(V)
Power Consumption	DC15V, 13W (SMPS 90~ 250V)
Resolution	380TV lines
Input Signal	Composite Video 75 Ohm 1Vp-p
External/Input Jack	Terminal Chime Bell
Dimensions	7.48 x 9.06 x 2.05 in / 190 x 230 x 52 mm
Weight	5.0 lb / 2.26 kg
Certifications	FCC, DHHS Subchapter J 21 CFR 1020.10