



HAWK-335CD

Aluminum Mini Color Weatherproof & Vandalproof Dome Camera, Surface Mount Type with adjustable Ball mounting system. 1/3" SONY SUPER HAD 500TVL & High Resolution Image Sensor Built-in. Remarkable Color reproduction.

Outstanding high Sensitivity picture quality under extreme low illumination All direction adjustable Ball mounting system built-in for easy installment.

Only 3" in diameter.

Vandal-Resistance Crystal clear polycarbonate dome cover

Accidental Surge and Shock Protection Circuit Built-in.

Reverse Polarity Power Protection and Wide electrical tolerance

Extremely Low Power Consumption & Wide Dual power tolerance

Vandalproof, Tamperproof ,Anodized Aluminum Housing, Polycarbonate Cover

Weatherproof(IP=66) for installing universal applications at Indoor/Outdoor

All parts replaceable by end user

European Stylish design & Scratch-Proof coating

HAWK-335CD

Specifications

Image sensor	1/3" Sony SuperHad Color CCD
Effective Pixels	768(H)X494(V)
Horizontal Resolution	500 TV Lines
Synchronizing system	Internal
Scanning system	525 Lines
Video output	1.0Vp-p Composite. 75 Ohms
S/N ratio	More then 48 dB (AGC Off)
Min. Illumination	0.3 Lux at F2.0
BLC	Automatic Control
White balance	2500°K - 9100°K Auto Tracing
Gain Control	4dB~35dB Auto
Gamma correction	r=0.45
Smear effect	0.01%
Shutter speed	1/60 - 1/100,000 sec
MTBF	40,000 hours
Power source	DC12V (9 -15V)
Operation current	110mA w / regulated 12VDC
Lens Standard	3.6mm
Optional Lenses	2.9mm, 4.3mm, 6mm, 8mm
Operating Temperature	14° F~135° F
Humidity	Within 90% RH
Output Termination	2 Feet Shield Cable with BNC for Video, DC Jack for Power (STD)