

HINT13D7G

3.6 fixed lens


Features

- 650 lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier3™ @ 512x)
- Chameleon Cover: Snap-on cover converts the housing from standard dark grey to decorator white and can be painted to match any décor.
- HLC Enhances backlight performance
- Full OSD operation
- Wall or ceiling mount
- S/N Ratio more than 52dB (weight on)
- Tamper resistant, can withstand hits from a 10 lb. sledgehammer!
- Weather resistant operation
- 5 year warranty

Now with Presets:
Outdoor, Indoor, Elevator,
Lobby, Hallway & Dark



Shown with included paintable, snap-on Chameleon™ cover



Specifications

Image Sensor	1/3" Sony Super-HAD™ CCD
Resolution	650 TV lines
Minimum Illumination	Shutter: 0.03 lux Intensifier3™: 0.00002 lux
Total Pixels	811 (H) x 508 (V)
Effective Pixels	768 (H) x 494 (V)
Scanning Frequency	15.734kHz (H) & 59.94Hz (V)
Scanning System	2:1 interlace
Synchronization	Internal
S/N Ratio	More than 52dB
Video Output	CVBS: 1.0Vp-p / 75 Ohms
Electronic Shutter Speed	Auto / AFLK 1/60 sec. - 1/90,000 sec.
OSD	Available
WDR	On / Off (level adjustable)
Backlight Compensation	BLC / HLC / Off
Day & Night	Color / BW / Auto
Gain Control	High / Middle / Low / Off

White Balance	ATW1 / ATW2 / ATW set / Manual
Intensifier3™	Auto / Off (selectable x2 - x512)
Motion Detection	On / Off (8 programmable zones)
Privacy Masking	On / Off (8 programmable zones)
Speco DNR	On / Off (level adjustable)
Digital Zoom	On / Off (1x - 8x)
DIS	On / Off
Sharpness	On / Off (level adjustable)
Flip / Mirror	On / Off
Power Supply	12VDC (power supply not included)
Power Consumption	210mA
Operating Temperature	-20° F - 122° F
Dimensions	3.07" (H) x 4.33" (Dia.)
Weight	1.54 lbs.

Optional Accessory



PSW5
Power Supply



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/22/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880

www.specotech.com