



Color Day/Night Weatherproof Camera



HT7715DNV
HT7715DNVW (white)

Features

- 1/3" Sony Super-HAD™ HQ-1 DSP CCD sensor
- 560 lines of resolution
- Split Glass Technology to avoid IR reflections
- 4-9mm Auto Iris DC Varifocal Lens
- LUX level dip switch adjusts day/night settings to your requirements
- Dual voltage operation
- 18 Built-in IR LEDs (80' Range - depending on scene reflection) & CDS sensor for day/night performance
- Controls for BLC, ELC, F/L and L/L
- Video Test Connector for easy installation
- Built-in heater extends operating range and avoids condensation
- Weatherproof operation
- Excellent low light level performance - 0.03 Lux in existing light, 0.0 Lux with IR LEDs

Specifications

Image Sensor	1/3" Sony Super-HAD™ HQ-1 DSP CCD
Resolution	560 lines
Minimum Illumination	0.03 lux (IR off) 0.00 lux (IR on)
Lens	4-9mm Auto Iris DC Varifocal Lens
CDS Sensor	Photoconductive cells - adjustable
Electronic Shutter	1/60 - 1/100,000 seconds
Video Output	1.0 Vp-p into 75 ohms composite
TV System	NTSC
Scanning System	2:1 Interlace
Sync System	Line locked/ adjustable V-phase Line lock/internal on-off
S/N Ratio	More than 60 dB
Gamma Characteristic	0.45
Power Supply	24 Volts AC, 12 Volts DC- dual voltage
Power Consumption	600mA
Operating Temperature	-20°F to 122°F - RH 95%
Dimensions	2.4" W x 2.25" H x 7" L
Weight	1 lb.

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880