


speco technologies®

Intensifier™ 2 Series Weatherproof/Tamperproof Dome Camera with Chameleon™ Cover

Intensifier™ 2 Series	See in the dark without IR LEDs
Featuring HLC	For enhanced backlight operation
Digital Image Stabilization and Advanced Noise Reduction Circuitry	Eliminates blur
Relay Outputs	Triggered by built-in video motion detection
580 Lines of Color Resolution	Extreme resolution for extreme detail
Chameleon™ Cover	Snap-on cover can be painted to match any décor
Dual Voltage Operation	12V DC or 24V AC (auto-sensing) with line-lock
Wall & Ceiling Mount	3-way internal mount
Weatherproof/Tamperproof	Indoor or outdoor, meets all your surveillance needs

shown with
Chameleon™ Cover



**All Menu Functions Controlled
Using An Internal Joystick**

HT7246iHR

2.8-11mm Auto Iris Varifocal Lens

HT7247iHR

9-22mm Auto Iris Varifocal Lens



Specifications

Horizontal Resolution	580 TV lines
Intensifier™	Built-in (selectable from 2x to 256x)
Image Device	Sony HQ-1™ with a customized DSP behind it
Min. Object Illumination	0.002 lux (Intensifier™) 0.03 lux (shutter)
Effective Picture Element	410K
HLC/SLC (Speco Light Compensation)	Advanced backlighting controls
White Balance	W-ATW / S-ATW / AWC / MANUAL
Electronic Shutter	1/60-1/100,000 seconds
AGC	AGC-L, AGC-M, AGC-H, OFF selectable
Video S/N Ratio	Greater than 52db
Weatherproof Standard	IP66
Mechanical construction	Aluminum composite/polycarbonate - tamper resistant
Operating Environment	-20°F to 120°F
Video Signal Output	1.0V(p-p) NTSC composite, 75 ohms / BNC Connector + Video Test Connector
Power Consumption	230mA (DC) / 3.8W (AC)
Power Supply	12V DC & 24V AC (Dual Voltage)
Weight	24 ounces
Scanning System	2:1 interlaced 525 lines / 60 fields / 30 frames
Synchronization	Internal / line lock selectable through OSD
S-DNR Video Noise Reduction	ON / LOW / MIDDLE / HIGH
Motion Detection	8 zones - relay outputs
On-Screen Display (OSD)	Built-in
Privacy function	ON / OFF (8 Programmable Zones)
Dimensions	.629" W x 3.89" H

Optional Accessories:

CVCTPEXT	Junction Box used for connections and/or conduit applications
7246WMT	Weatherproof wall mount for use with many Speco Dome Cameras

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880