

Glacier™ Series / Intensifier3™ Bullet Camera

See Color In Almost Complete Darkness Without IR LEDs

DUAL VOLTAGE

INDOOR/OUTDOOR

FULL OSD

HTINTB8G

HTINTB8GW

HTINTB10G

HTINTB10GW

2.8-12mm auto iris varifocal lens, dark grey housing

2.8-12mm auto iris varifocal lens, white housing

9-22mm auto iris varifocal lens, dark grey housing

9-22mm auto iris varifocal lens, white housing

Features

- 650 lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Automatic thermostatic sensor
- Minimum illumination 0.00002 lux (Intensifier3™ @ 512x)
- 12VDC / 24VAC dual voltage operation
- Full OSD operation
- -40° F with Glacier heaters
- External controls for zoom & focus
- Weather resistant operation
- EZ mount system simplifies installation
- 5 year warranty

Now with Presets:
Outdoor, Indoor,
Elevator, Lobby,
Hallway & Dark



Specifications

Image Sensor	1/3" Sony Super-HAD II™ CCD
Resolution	650 TV lines
Minimum Illumination	CDS Off: 0.15 lux CDS On: 0.00002 lux
Total Pixels	811 (H) x 508 (V)
Effective Pixels	768 (H) x 494 (V)
TV System	NTSC
Scanning Frequency	15.734kHz (H) / 59.94Hz (V)
Scanning System	2:1 interlace
Synchronization	Internal
S/N Ratio	More than 52dB
Video Output	CVBS: 1.0Vp-p / 75 Ohm
Electronic Shutter Speed	1/60 sec. - 1/120,000 sec.
OSD	Available
WDR	On / Off (level adjustable)
Backlight Compensation	BLC / HLC / Off
Day & Night	Color / BW / Auto
Gain Control	High / Low / Off
White Balance	ATW / Outdoor / Indoor / Manual AWC (1,700°K - 11,000°K)
Intensifier3™	Auto / Off (selectable 2x - 512x)
Motion Detection	On / Off (8 programmable zones)
Privacy Masking	On / Off (12 programmable zones)
Speco DNR	On / Off (level adjustable)

Digital Zoom	On / Off (1x - 16x)
DIS	On / Off
Sharpness	On / Off (level adjustable)
Flip / Mirror	On / Off
Power Consumption	12VDC, 250mA (heater off) 800mA (heater on) 24VAC, 100mA (heater off) 380mA (heater on)
Power Supply	12VDC / 24VAC (dual voltage) (power supply not included)
Operating Temperature/	
Humidity	14° F - 122° F / RH 95% max., -40° F with Glacier heaters
Storage Temperature/	
Humidity	-4° F - 140° F / RH 95% max.
Dimensions	3.46" (W) x 3.43" (H) x 11.22" (D)
Weight	3 lbs.

Optional Accessories



PSW4 or PSDC24
24VAC or 12VDC
Power Supply



CVCJBB
Bullet Camera
Junction Box



INTJBS
Square
Junction Box



INTCM
Corner/Pole
Adaptor