

### **Overview**

Altronix new HubWayLDH8S Active UTP Transceiver Hub transmits UTP video and RS422/RS485 data over a single CAT-5 (or higher) structured cable. Unit provides for 8 camera channels in a space saving 1U EIA 19" rack mount chassis which may be wall or shelf mounted. Video transmission range is up to 3000 ft. max. per channel. Units are compatible with fixed or PTZ cameras. An optional HubSat4S Passive UTP Transceiver Hub with Integral Camera Power can be used as an accessory module to transmit video from up to 4 cameras over a single CAT-5 (or higher) structured cable back to the HubWayLDH8S. In addition, the HubSat4S provides power to these cameras locally to eliminate the possibility of voltage drop associated with long cable runs.



### **Specifications**

#### ***Input:***

- 115VAC 50/60Hz, 2 amp  
or 230VAC 50/60Hz, 1.25 amp.
- Primary fuse is rated at 5 amp/250V.

#### ***Video:***

- Eight (8) channels of video over twisted pair up to 3000 ft.
- Eight (8) 75 ohm video outputs.

#### ***Data:***

- RS422/RS485 data inputs.

#### ***Visual Indicators:***

- AC input power indicator.
- Eight (8) individual video LED indicators.

#### ***Features:***

- Picture and Gain control.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Unit can be rack, wall or shelf mounted.
- 1U EIA 19" rack mount chassis.

#### ***Optional Accessories:***

- HubSat4S allows transmission of up to four (4) video signals over a single CAT-5 (or higher) structured cable.

#### ***Shipping Weight (approximate):***

- HubWayLDH8S: 7.95 lbs.

### **Models**


#### ***HubWayLDH8S***

Active UTP Transceiver Hub.

**HubWay® LDH8S Rack Chassis Dimensions**

1.625”H x 19.125”W x 8.5”D

REAR



TOP & BOTTOM



FRONT

