

On-Q

IC5003-AB

Selective Call Intercom Video Door Unit, Antique Brass - IC5003-AB



This innovative door unit, housed in an attractive weatherproof finish, includes a wide-angle color camera for front door monitoring. When integrated with the On-Q camera system LCD, the doorbell press enables the image from the door unit camera to appear on the LCD screen. The image can also appear on any TV connected to a TV display port.

FEATURES

- Crisp color image also performs well in low-light conditions.
- Includes up to 20 digital door tones.
- As part of the [Studio collection](#) this innovative video door unit enhances the curb appeal of any home.
- Installs in a standard double gang opening with simple RJ45 plug design for easy installation and troubleshooting.

Specifications

CONNECTORIZED INFO

Pinning:

Pin 1	24 VDC Out
Pin 2	GND
Pin 3	Audio (+)
Pin 4	COMM A
Pin 5	COMM B

On-Q

IC5003-AB

Pin 6 Audio (-)
Pin 7 VIDEO INPUT
Pin 8 GND

DIMENSION INFO

Product Weight U S: 1.5 lbs
Overall Dimensions U S: 5.1" H x 4.5" W x 1.8" D
Weight: 1.5 lb

GENERAL INFO

Color: Antique Brass
Discontinued: No

TECHNICAL INFO

Viewing Angle: Horizontal: 105 degrees; Vertical: 80 degrees
Humidity: Up to 90% RH (non-condensing)
Material: Cast; Zinc Alloy
Operating Temperature Celcius: -25 to 55 degrees
Firmware Update: 16 Pin Header Connector
Power Requirements: +24Vdc, +/-1.5Vdc, 0.15A max
Q Link Selective Call Ports: RJ-45
Cat5 Cable Rating: CAT5 UTP, 4 pair solid conductor (24 AWG)
Operating Temperature Fahrenheit: -13 to 131 degrees
Storage Temperature: -45 to 85°C (-49 to 185°F)