

IQeye Sentinel

Megapixel Outdoor IP Camera

Features

- > Resolutions up to 5 MP, HD1080p (832)
- > H.264 Main Profile + MJPEG Compression
- > 30 fps @ 1.3 MP, 10 fps @ 5 MP
- > 30 fps @ HD1080p (832)
- > Day/Night Movable IR Filter on 85x and 832N
- > Lightgrabber™ II Low-light Feature
- > Power Over Ethernet, 12-24VDC, 24VAC
- > IP66 / NEMA 4 Outdoor Enclosure
- > Outdoor Camera with Mounting
- > ONVIF and PSIA Compliant (832)
- > 3 Year Warranty

Available in 1080p H.264 Main profile and 1.3, 2, 3 and 5 MJPEG models, the Sentinel Series provides the flexibility to monitor any outdoor area, including parking lots, building exteriors, campus perimeters and warehouses. The all-weather Sentinel Series cameras were designed with the installer in mind. The innovative features like Ethernet terminal punch-down (eliminating the need to terminate with an RJ45 connector) and brass camera hangers allow the installer to work with both hands at once saving time and money while eliminating frustration. The wall, ceiling and parapet mounting options, rugged aluminum construction and IP66 weather resilience allow the camera to be installed virtually anywhere, especially harsh environments. At less than 7W power consumption, the Sentinel can be fully operational using only Power-over-Ethernet.



IQ inVision 

33122 Valle Road
San Juan Capistrano, CA
92675-4853
USA

toll free within US 877.850.0805
phone +1.949.369.8100
fax +1.949.369.8105

www.iqeye.com

Specifications

Video

| | |
|--|--|
| Compression | H.264 (832 Only) and MJPEG |
| H.264 Profile | Main (832) |
| Sensor | 1/3" CMOS 1 MP, HD1080p 1/2" CMOS for 2 MP and 3 MP 1/2.5" CMOS for 5 MP |
| JPEG Compression Quality Settings | User Configurable |
| Shutter Speed | Auto/Programmable/Fixed |
| Image Settings | Saturation, Contrast, Brightness, Sharpness, Lightgrabber™ II |
| Exposure | User Configurable |
| White Balance | Auto/Programmable |
| Backlight Compensation | Auto |
| IR Range | 800 to 940 nm |

Features

| | |
|------------------------------|--|
| Virtual Cameras | User Configurable Windows (80x, 85x) |
| Privacy Mask | User Configurable Windows (80x, 85x) |
| Motion Detection | User Configurable Windows |
| Access Hours | User Configurable |
| Time Lapse Recording | User Configurable |
| Event Based Recording | User Configurable |
| Cropping | User Configurable Windows (80x, 85x) |
| Flip and Rotate | 90, Horizontal, Vertical |
| Analog Service Port | NTSC/PAL |
| Focus Assist | IQfocus (80x, 85x) |
| Analytics Ready | Yes |
| On-Camera IQapps | IQaccess, IQauthenticate, IQnightlight, IQrecorder on 80x/85x) |

System Integration IQfinder, IQmanager, IQsentry, (ONVIF, PSIA on 832)

Network

| | |
|----------------------------|---|
| Supported Protocols | TCP/IP, HTTP, DHCP, UDP, RTP, RTSP, DNS, ARP, ICMP, NTP, SNMP, FTP, SMTP, Telnet (HTTPS, UPnP, ZeroConf, APIPA, UDP multicast, CIFS on 832) |
|----------------------------|---|

Password Protection Secure Multi-level

Input/Output

| | |
|--------------------------|--|
| Input Power | Power over Ethernet 802.3af Class 2, 24 VAC, 12-24 VDC |
| Power Consumption | < 7W (typical) |
| AC Lighting | 50 Hz/60 Hz Selectable |
| Network Interface | RJ45 10Base-T/100Base-TX |
| Physical I/O | 1 input, 1 output |


Misc

| | |
|----------------------------------|---|
| Ingress Protection Rating | IP66, NEMA 4 |
| Approvals | FCC, CE |
| Temperature Range | -22°F to 122°F, -30°C to 50°C |
| Weight (grams) | 2839 g |
| Warranty | 3 years |
| Lens Options | V3 Wide Angle Lens 1/2" CS, 4.5-10 mm, F1.6, IR V4 Telephoto Lens 1/3" CS, 5-50 mm, F1.3 V6 Telephoto Lens 1/2" CS, 12-40 mm, F1.8, IR V7 Wide Angle Lens 1/2" CS, 4-12 mm, F1.4, IR W2 Wide Angle Lens 1/2" CS, 4-12 mm, F1.4 IR |


| | |
|--------------------|--|
| Accessories | IQ800-PMA Pole Mount Adaptor IQ800-JBC Junction Box Cover IQ800-JB+C Junction Box with Cover |
|--------------------|--|

| | Part Number | Max Resolution | Max Framerate | Min Illumination | Compatible Lens |
|---------------------------------------|-------------|-----------------------|---------------|--------------------------------|-----------------|
| H.264 Day/Night | IQ832N | HD1080p - 1920 x 1080 | 30 fps | Color: 0.3 lux, B/W: <0.05 lux | V6, V7, W2 |
| H.264 Day Only | IQ832S | HD1080p - 1920 x 1080 | 30 fps | Color: 0.3 lux | V6, V7 |
| MJPEG Day/Night with IR filter | IQ851 | 1 MP - 1280 x 1024 | 30 fps | Color: 0.2 lux, B/W: <0.05 lux | V3, V6 |
| | IQ852 | 2 MP - 1600x1200 | 20 fps | Color: 0.2 lux, B/W: <0.05 lux | V6, V7, W2 |
| | IQ853 | 3 MP - 2048 x 1536 | 12 fps | Color: 0.3 lux, B/W: <0.05 lux | V6, V7, W2 |
| | IQ855 | 5 MP - 2560 x 1920 | 10 fps | Color: 0.3 lux, B/W: <0.05 lux | V6, V7, W2 |
| MJPEG Day Only | IQ811 | 1 MP - 1280 x 1024 | 30 fps | Color: 0.2 lux | V4, V7 |
| | IQ802 | 2 MP - 1600 x 1200 | 20 fps | Color: 0.2 lux | V6, V7 |
| | IQ803 | 3 MP - 2048 x 1536 | 12 fps | Color: 0.3 lux | V6, V7 |
| | IQ805 | 5 MP - 2560 x 1920 | 10 fps | Color: 0.3 lux | V6, V7 |


Dimensions



Side



Front



Back