

IQeye PRO LINE



IQeye Alliance™ Series

PRODUCTS



IQeye Alliance Series

The IQeye Alliance Series is a fully-integrated vandal-resistant megapixel dome camera line. With easy installation and a variety of models to choose from, the IQeye Alliance is ideal for many applications.



IQeye Alliance Day/Night Series

The IQeye Alliance Day/Night Series offers TRUE day/night functionality for the most challenging environments — delivering clear, crisp megapixel quality video even in very dimly-lit areas.



IQeye Alliance H.264 Series

This IQeye Alliance model utilizes H.264 compression method to efficiently lower file sizes while still delivering high-quality images at megapixel resolutions. Also supports audio synchronization and works well in challenging conditions.



IQeye Alliance Extreme Temperature Series

The IQeye Alliance Extreme Temperature Series is a vandal-resistant dome camera designed to withstand the harshest weather conditions — including hot, cold and wet environments.

Enjoy high-quality images with the full-integrated, vandal-resistant megapixel dome camera line, the IQeye Alliance. Its features include high-resolution images from VGA to 5.0 megapixels, full PoE capability and a 3-axis gimbal. The IQeye Alliance's solid aluminum construction and impact-resistant polycarbonate bubble make it tough enough for any environment and its low-profile design gives it the perfect balance between discreet and deterrent.



Camera weight: 27.5oz (780.5g)

IQinVision 
www.iqeye.com



IQeye PRO LINE

IQeye Alliance™ Series

FEATURES

- Vandal-Resistant, Low Profile Surface Mount Housing
- Interior or Exterior Security Video Solution
- Optional H.264 with Audio
- Full 3-axis Gimbal with Pivoting, Hinged Lens Shroud
- 64 Independent Video Streams with IQcameo™
- Analog Video Out for Installation / Set-up
- Extra Analog Video for Public View Monitor
- SDHC Card Slot for On-camera Storage
- -22°F/-30°C to 122°F/50°C on Extreme Temperature Models
- VGA Resolution @ 30 fps
- 1.3 Megapixels @ 15 fps
- 2.0 Megapixels @ 15 fps
- 3.1 Megapixels @ 12 fps
- 5.0 Megapixels @ 10 fps
- LIGHTGRABBER™ II Low-light Feature
- IEEE 802.3af - Power-over-Ethernet, or 12-24 VDC
- Low 2.5 watts Power Consumption
- Digital Image Cropping
- Include/Exclude Exposure Window, Privacy Zones
- IP66/NEMA 5 (Outdoor/Extreme Temperature Models)

Easy Installation Design

Like all IQinVision products, the IQeye Alliance Dome Camera system is an innovative surveillance camera that is designed to save time and money on installation and maintenance. A key highlight is the industry-first, pivoting hinged shroud that automatically stays aligned with the camera position, yet easily swings away to make the camera positioning a breeze.

On-Camera Recording

The IQeye Alliance Series features a built-in slot for an SDHC memory card enabling direct, on-camera recording. Perfect for a back-up solution to any system or for smaller applications. And, with IQrecorder™ embedded directly in the camera, you'll be able to utilize many sophisticated features including pre-event/post-event recording, time-date search and AVI export functionality.

IQrecorder

Available with every IQeye PRO LINE camera, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage with no client software. User-friendly features include simultaneous playback and live viewing, day-by-day scheduling, a brand new playback interface with DVD-like controls.

CUSTOMIZED CONFIGURATIONS

SERIES	RESOLUTION OPTION	STANDARD or DAY/NIGHT	INTERIOR/EXTERIOR	LENS OPTION
IQA1 – IQeye Alliance	0 – VGA Camera, 30 fps, 0.2 lux 1 – 1.3MP Camera, 15 fps, 0.2 lux 2 – 2.0MP Camera, 15 fps, 0.2 lux 3 – 3.1MP Camera, 12 fps, 0.3 lux 5 – 5.0MP Camera, 10 fps, 0.3 lux	S – Standard N – Day/Night	I – Interior E – Exterior X – Extreme Temperature	B2 – Wide Varifocal Lens B3 – Wide Varifocal Lens B4 – Wide Varifocal Lens B5 – Day/Night Varifocal Lens B6 – Day/Night Varifocal Lens
IQA2 – IQeye Alliance, H.264	0 – VGA Camera, 30 fps, 0.2 lux 1 – 1.3MP Camera, 15 fps, 0.2 lux 2 – 2.0MP Camera, 15 fps, 0.2 lux 3 – 3.1MP Camera, 12 fps, 0.3 lux 5 – 5.0MP Camera, 10 fps, 0.3 lux	S – Standard N – Day/Night	I – Interior E – Exterior	B2 – Wide Varifocal Lens B3 – Wide Varifocal Lens B4 – Wide Varifocal Lens

ACCESSORIES

	IQA-BBL - Alliance Interior/Exterior Vandal Dome Replacement Bubble and Trim Ring Assembly		IQAE-BOX - Alliance Exterior Vandal Dome Back Box for Existing Interior Models
	IQAI-PLT - Alliance Replacement Interior Mounting Plate Wall Mount Adapter		IQA-WM - Alliance Interior/Exterior Vandal Dome Wall Mount Adapter

NOT ALL CONFIGURATIONS INDICATED ARE POSSIBLE. Contact IQinVision for a complete list of IQeye Alliance configurations.

IQinVision