

Features

H.264 HD720p or HD480p @ 30 fps MJPEG VGA @ 33 fps, HD720p @ 25 fps, 1.3 MP @ 18 fps, 2.0 MP @ 17 fps Low-light Performance (0.2 lux) Power-over-Ethernet 3-Axis Gimbal Digital Image Cropping On-Camera Motion Detection Low-power Simultaneous H.264 & MJPEG Streams* Two-Way Audio* Built-in Mic* External Mic/Speaker Connection* Bubble Size <3"/74mm in Diameter Megapixel Lens Wide Dynamic Range Cast-aluminum Tamper-proof Option Wall and Pendant Mount Options Extreme Wide and Telephoto Lens Options * H.264 Models Only

Standard Camera Models

IQD30SI-F1 — H.264 HD480p/VGA, MP Fixed Lens IQD40SI-F1 — MJPEG HD480p/VGA, MP Fixed Lens IQD31SI-F1 — H.264 HD720p, MP Fixed Lens IQD41SI-F1 — MJPEG HD720p/1.3 MP Resolution, MP Fixed Lens IQD42SI-F1 — MJPEG 2.0 MP Resolution, MP Fixed Lens

Interior Vandal Camera Models

IQD30SV-F1 — H.264 HD480p/VGA, MP Fixed Lens IQD40SV-F1 — MJPEG HD480p/VGA, MP Fixed Lens IQD31SV-F1 — H.264 HD720p, MP Fixed Lens IQD41SV-F1 — MJPEG HD720p/1.3 MP Resolution, MP Fixed Lens IQD42SV-F1- MJPEG 2.0 MP Resolution, MP Fixed Lens

IQeye Mini Dome Accessories

IQD4-WG/IQD4-WB** - Wall Mount, Beige or Black IQD4-PG-5/IQD4-PB-5** - Pendant Mount, Beige or Black, 5 Pack IQD4-F2-5/IQD4-F3-5 — Lens Pack, 2.8mm or 8mm, 5 Pack ** Standard Camera Models Only

IQeye Mini Dome High-resolution **IP Cameras**

The IQeye Mini Dome offers high performance in a compact, versatile and attractive minidome package. It is available in standard and interior vandal models from VGA to 2.0 megapixel resolutions, making it the highest resolution mini-dome camera in its class.

The IQeye Mini Dome camera is designed for discreet indoor use. Each camera includes black and beige trim rings to blend into the most demanding indoor architectural installations. These ultra lightweight cameras easily mount to ceilings or walls, and the true 3-axis gimbal, locking shroud and Power-over-Ethernet design saves time and money on installation and maintenance. Optional accessory kits include wall and pendant mount, wide & telephoto lenses.

The IQeye Mini Dome is completely Power-over-Ethernet, so all that is required for installation is connecting to a PoE enabled Ethernet cable and the IQeye Mini Dome is ready to go.



Standard Camera weight 8.8oz (249.5g) Interior Vandal Camera weight 10.1 oz (287.0g)



33122 Valle Road San Juan Capistrano, CA92675-4853 USA toll free within US 877.850.0805 phone +1.949.369.8100 fax +1.949.369.8105

© 2010 IQinVision, Inc. 300-2104 Rev. D

www.iqeye.com

