



IQeye510 Wide Dynamic Range IP Camera

Ideal for high-speed applications like traffic, transportation and casinos, the IQeye510 network Camera's global shutter technology captures high-resolution images without the distortion that occurs with interlaced technology. The Wide VGA format lets you cover a wider area, so deployment is cost-effective, and Wide Dynamic Range lets you capture all the details in the most challenging lighting environments.

The IQeye510 delivers real-time, high-quality video and best-in-class low-light performance in an attractive, low-profile industrial package. Installation and maintenance is simple and inexpensive with features like Power-over-Ethernet and IQfocus™ utility.

Like every IQeye, the IQeye510 is built on IQinVision's world class operating system that offers unmatched network stability and reliability, so you *never miss a thing*.

Features


- Global Shutter
- Wide Dynamic Range, up to 100dB
- Wide VGA Resolution (752 x 480) @ 60 fps
- Power-over-Ethernet, AC or DC
- Low-light Performance (0.4 lux)
- LIGHTGRABBER™ II Low-light Feature
- Digital PTZ with No Moving Parts
- Multi-zone Motion Detection
- Digital Image Cropping
- Advanced Bandwidth Management Tools
- Low 2.5 watts Power Consumption
- Include/Exclude Exposure Window, Privacy Zones

Available Camera Models

IQ510 – WVGA Resolution, 60 fps, 0.4 lux

Accessories

X2 – Outdoor Housing, IP65/NEMA 4



Camera weight (without lens): 6oz (160g)

IQinVision 

33122 Valle Road
San Juan Capistrano, CA92675-4853 USA
toll free within US 877.850.0805
phone +1.949.369.8100
fax +1.949.369.8105

www.iqeye.com

© 2009 IQinVision, Inc. 300-2102 Rev. A.