



Color Box Cameras

IV-BCH5352

Features:

- . 1/ 3 inch interline transfer CCD
- . 540 TV Lines
- . Digital noise reduction
- . Day and night
- . 0.002 lux/B&W
- . OSD



SPECIFICATION	IV-BCH5352
Power Source	170mA(AC 24V) / 260mA(DC 12V) 160mA(DC 12V)
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Size	1/ 3 inch interline transfer CCD
Scanning System	2:1 Interlace
Synchronization	INT/LL Selectable, INT, 0~359°(Adjustable)
Frequency	Horizontal:15.734 KHz Vertical :59.94
Resolution	540 TV Lines
Video Output	1.0Vp-p/75(Video 0.714Vp-p Sync 0.286Vp-p)
S/N (Y signal)	50dB (AGC Off)
Min. Illumination	0.3Lux/F1.2(Color), 0.1Lux/F1.2(B/W), 0.002Lux(Sens-up)
COLOR	ON / AUTO
Gain Control	OFF / LOW / MIDDLE / HIGH
White Balance	ATW / AWC / MANUAL(1,800°K~10,500°K)
Electronic shutter speed	AUTO / MANUAL(1/60~1/120,000)
Sens-Up	OFF / AUTO
O.S.D	Built-in
Motion Detection	ON / OFF (4 Programmable Zone)
DNR	OFF / LOW / MIDDLE / HIGH(Noise Reduction)
MIRROR	Built-in (Horizontal Image Inversion)
Privacy Function	ON / OFF (4 Programmable Zone)
IRIS Control	DC / VIDEO
Lens Mount	C/CS Mount (Screw Lock)
Operating temperature	-10°C ~ +50°C
Humidity	30~90% RH
Weight	360g