



Outdoor IR Bullet Camera

IV-BIR123C

Features:

- . Day and Night
- . 0 Lux (with IR LED ON)
- . Excellent image quality
- . IR LED effective range reaches up to 60 ft
- . Waterproof IP66
- . Metal shield



SPECIFICATION	IV-BIR123C
Pick up Element	1/3" Sony CCD
Number of Pixel	NTSC: 768(H) x 494(V)
Resolution	480 TVL
Lens	3.6mm
S/N Ratio	More than 48dB
Clock Frequency (MHZ)	26.636
Scanning System	2:1 interlace
Min. Illumination	0 Lux (with IR LED ON)
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	1/60 to 1/100,000 sec
Gamma Characteristic	0.45
IR Distance	60 ft (with 23 Unit infrared LEDs)
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Video Output	1.0 Vp-p, 75Ω
Auto Gain Control	Auto
Power/ Current	DC 12V (±10%)/ 300mA
Water Resistance	IP66
Storage Temperature	-22°F~140°F RH95% Max
Operating Temperature	14°F~122°F RH95% Max
Dimension (WxHxD)	8.97"x3.8"x3.3"
Weight	1.17 lbs