



Vandal-Resistant IR Dome Camera

IV-DV502IRS

Features:

1/3" SONY Super HAD CCD

Day/Night Function

620 TVL

0.3 Lux @ F1.2 (Color)

Sens-up (x256)

35 IR LED (0.0 Lux IR on), Viewing Distance 100ft

On Screen Display Menu

3DDNR

Privacy Zone

Motion Detection

4-Axis, true 160 degree viewing angle

IP68



SPECIFICATION	IV-DV502IRS
Resolution	620 TVL
Sensor	1/3" SONY Super HAD CCD
Total Pixels	NTSC: 811(H)x508(V) 410k Pixels; PAL: 795(H)x595(V) 470k Pixels
Effective Pixels	NTSC 768(H)x494(V) 380k Pixels; PAL: 752(H)x582(V) 440k Pixels
Scanning System	2:1 Interface
Synchronization	Internal
Frequency	NTSC:Horizontal15.734kHz/ Vertical: 59.94Hz; PAL:Horizontal 15.625kHz/Vertical 50Hz
S/N	More than 50dB (AGC Off)
Video Output	CVBS 1.0Vp-p/75ohm
Min. Illumination	0.3 Lux @ F1.2 (Color), 0.03 Lux (B/W), Sens-up(x256), 0.0 Lux (IR on)
White Balance	ATW/ ATC/ Manual (2100k ~ 10500k)
ES Speed	Auto/Manual (NTSC:1/60sec~1/120000sec;PAL:1/50sec~1/120000sec)Selectable/Flickerless
Lens	2.8-12mm
O.S.D	Built-In
Backlight Compensation	Low/ Middle/ High/ Off Selectable
Gain Control	Low/ Middle/ High/ Off Selectable
3D Digital Noise Reduction	Low/ Middle/ High/ Off Selectable
Day/Night	Auto/On
Motion Detection	On/ Off 64 Grids
Privacy Zone	On/ Off 4 Zones
MIRROR	On/ Off
Operating Temp.	-30C~50C / -22F~122F, 30%~80% RH
Storage Temp.	-30C~60C / -22F~140F, 20%~90% RH
Power	DC 12V/ AC 24V
Protection Rating	IP 68