



# Vandal-proof Outdoor Dome Camera

## IV-DV502V

### Features:

- . 1/3" Sony Super HAD CCD
- . 560 TV Lines of Resolution
- . 2.8mm ~ 12mm DC Auto Iris Varifocal Lens
- . Day and Night Function
- . 0.3 Lux at F1.2 (Color)
- . 0.03 Lux (Black & White)
- . On Screen Display Menu
- . Motion Detection
- . Privacy Zone
- . Mirror
- . Service Video Output
- . 12Volt DC / 24 Volt AC Dual Voltage
- . IP 68



OSD CONTROL



SERVICE VIDEO OUT



SHOCK RESISTANT



| SPECIFICATION             | IV-DV502V                                            |
|---------------------------|------------------------------------------------------|
| Resolution                | 560 TV Lines                                         |
| Sensor                    | 1/3 inch SONY Super HAD CCD                          |
| Lens                      | 2.8mm ~ 12mm DC Auto Iris Varifocal Lens             |
| Total Pixels              | NTSC : 811(H) x 508(V) 410K Pixels                   |
| Effective Pixels          | NTSC : 768(H) x 494(V) 380K Pixels                   |
| Scanning System           | 2:1 Interface                                        |
| Synchronization           | Internal                                             |
| Frequency                 | NTSC : Horizontal: 15.734KHz / Vertical: 59.94Hz     |
| Signal to Noise Ratio     | More than 50 dB (AGC Off)                            |
| Video Output              | CVBS : 1.0Vp-p / 75 Ohm                              |
| Minimum Illumination      | 0.3 Lux at F1.2 (Color) / 0.03 Lux (Black & White)   |
| White Balance             | ATW / ATC / Manual (2,100°K ~ 10,500°K)              |
| Electronic Shutter Speed  | Auto / Manual; NTSC : 1/60 second ~ 1/120,000 second |
| On Screen Display Menu    | Built - in                                           |
| Backlight Compensation    | On / Off                                             |
| Gain Control              | On / Off                                             |
| Day & Night               | Auto / On                                            |
| Motion Detection          | On / Off; 64 Grids                                   |
| Privacy Zone              | On / Off; 4 Zones                                    |
| Mirror                    | On / Off                                             |
| Operating Temp / Humidity | -10° ~ 50° Celsius / 30% ~ 80% RH                    |
| Storage Temp / Humidity   | -20° ~ 60° Celsius / 20% ~ 90% RH                    |
| Power                     | 12 Volt DC / 24 Volt AC                              |
| Protection Rating         | IP 68                                                |