



Outdoor Vandal-Proof IR Dome

IV-DV6504IR

Features:

- . High Resolution 600TV Lines
- . Vandal Resistant Housing
- . Weatherproof (IP66)
- . True Day & Night (ICR)
- . 3 Axis Gimbal Bracket
- . Side & Rear Cable Entry
- . 2D DNR / IR SMART / D-WDR



Specification		IV-DV6504IR
Total Pixels		811(H) x 508(V)
Effective Pixels		768(H) x 494(V)
Sensor		1/3" Sony Super HAD II CCD
Scanning System		2:1 Interlace
Frequency		Horizontal :15.734KHzVertical : 59.94Hz
E L E C T R I C A L	Resolution	More than 600 TV Lines
	Video Output	1.0Vp-p Composite Signal (75ohm)
	S/N (Y signal)	52dB or more (AGC OFF)
	Min.Illumination	0 Lux for Infrared Lighting Conditions
	Gain Control	OFF / LOW / MIDDLE / HIGH
	White Balance	ATW1(2300°K~9500°K)/ATW2(2000°K~11000°K)/MANUAL
	Electronic shutter speed	1/60s - 1/100,000s
	Back light(BLC)	OFF / BLC / HLC Selectable
	2D-DNR	ON / OFF Selectable
	D&N Selection	AUTO / COLOR / BW / EXT
	D-WDR	ON / OFF Selectable(Level Adjustable 0~35)
	Dead Pixel(DPC)	OFF / Auto(Max 64points)
	IR SMART	ON / OFF Selectable(IR GAIN Level Adjustable 0~ 255)
	Motion Detection	OFF / ON(4Areas Selectable)
	Privacy Masking	OFF / ON(8Masks Selectable)
	Lens Shading(LSC)	ON / OFF Selectable(Level Adjustable 0~255)
	SHARPNESS	ON / OFF (Level Adjustable 0~30)
	O.S.D	Available
IR Range		30 IR LEDs
Lens Mount		2.8 ~ 11mm DC Auto Iris
Operating temperature/Humidity		14 °F ~ 122 °F / 0 ~ 80% RH
Power Supply		DC12V 110mA (CDS ON : 480mA)
Dimensions		5.70" (W) x 3.94" (D)
Weight		Appx. 1.25 lbs