



Weatherproof IR Bullet Camera

IV-W252-0VF

Features:

- . 1/3" High Sensitivity CCD
- . High Resolution 600 TVL
- . DC Iris Vari-focal Lens 3.8-9.5mm
- . Built-in IR LED 18EA
- . IR Visible Range : 60ft
- . Day&Night (ICR)
- . Min. Illumination : 0.00 Lux (IR LED On)
- . Weather Proof Housing
- . IP 66



SPECIFICATION	IV-W252-0VF
Signal System	NTSC
Scanning System	2:1 Interlace
Scanning Frequency(H)	15.734kHz
Scanning Frequency(V)	59.94Hz
Image Sensor	1/3" High Sensitivity CCD
Total Pixels Number	811(H) x 508(V) 410K
Effective Pixels Number	768(H) x 494(V) 380K
Horizontal Resolution	600 TVL
Video Output Level	1.0 Vp-p (75Ω, composite)
S/N Ratio	More than 48dB (AGC off)
Lens	DC Iris Vari-focal Lens 3.8-9.5mm
Angle of View	f=6mm: 60°
Min. Illumination	0.00 Lux (IR LED on)
White Balance	Auto
AGC	On/Off
BLC	On/Off
Flickerless	On/Off
Electronic Shutter Speed	1/60~100,000sec
IR LED & Sensor	850nm IR LED 18EA, Sensor 1EA
IR LED Lighting Distance	60 ft
Input/Output Connector	Power input(red jack), Video output(yellow jack)
Supplied Voltage	DC 12V
Operating Temperature	14°F~122°F (-10°C~50°C)
Dimensions	3.07"(Ø) x 6" (H) / 78.0(Ø) x 150.0(H) mm
Weight (Net)	Approx.28.2 oz / 800g