KONTOUR™ SERIES









(Shown with Apple® Cinema Display adapter, not included.)

WHAT YOU NEED TO KNOW

INSTALLING THE MONITOR MOUNT

The mounting surface thickness must be between 0.75 - 2.5" (19 - 63 mm).

MOUNTING PATTERNS

Compatible with 75 x 75 mm and 100 x 100 mm VESA* patterns.

QUICK-CONNECT INTERFACE

Easily attach and remove interface from mounting head without removing monitor - no tools necessary!



FEATURES

1 HEAVY DUTY DESIGN Sleek, solidly constructed forged aluminum arms.

2 ULTIMATE FLEXIBILITY Dynamic height adjustment using gas-spring technology for ideal positioning.

FAST INSTALLATION Simple 3-step installation and integrated quick-connect interface for easy mounting and maintenance.

4 CABLE MANAGEMENT Tool-free cable management covers for a clean, professional look.

5 CENTRIS* EXTREME TILT PATENTED FEATURE Tilts -75°/+10° for an ultimate ergonomic solution.

	SPECIFICATIONS	
	Depth from Back of Desk	2.09" (53 mm)
١	Max. Extension	19.9" (505 mm)
Т	ilt	-75° / +10°
H	leight Assist	13" (330 mm)
V	Veight Capacity	5 - 25 lbs (2.3 - 11.3 kg)
-	Colors	Black, Silver

RECOMMENDED ACCESSORIES



KRA202 Grommet Accessory



KRA300 ■ K1 Series Laptop Tray

For a complete list of monitor mount accessories see page 121.

TECHNICAL DRAWINGS







