

HDMI® via Dual CAT5e/6 Matrix Switchers

KD-4X4XC **NEW**

4 Inputs to 4 Outputs HDMI via Dual CAT5e/6 Matrix Switcher
Includes (4) KD-CATHD4X4Rx Baluns




Key Features

- Full switching of 2 independent matrixes: HDMI Audio/Video, one-directional IR Tx to Rx
- Simultaneous availability of HDMI and CAT5e/6 outputs
- Supports all SD, HD, and VESA (VGA, SVGA, XGA, WXGA, SXGA, UXGA) resolutions up to 1080p (60Hz & 50Hz)
 - SD & HD: 480i, 480p, 720p, 1080i, 1080p
 - VESA / VGA (RGBHV): From 640x480p up to 1920x1200p
- Supports lossless compressed digital audio:
 - Dolby® TrueHD, Dolby® Digital Plus and DTS™-HD Master Audio
- Internal EDID Library features 9 default EDID configurations, in addition to Native EDID data for any Output/Display
- Light Buffer Technology (LBT™) dynamic signal re-clock

Key Benefits

- Transmits 1080p/60Hz up to 75 ft. 1080i and all lesser resolutions up to 100 ft. when used with included KD-CATHD4X4Rx receiver Baluns
- 2 active outputs per zone provide 8 total outputs (4 HDMI and 4 CAT5e/6) in a 4X4 configuration enabling flexible integration options
- IR signals may be routed from your control system, through the switch to your display location over CAT5e/6 for full control of your display or other remotely located devices
- Serial IR, Optical IR, Front Panel & RS-232 control
- Supports major control systems such as Compass Control®, AMX®, Control4®, Crestron®, RTI®, Universal®



**CHAMPION
SERIES™**



Advanced HDMI® Features

- 3D – Capability to pass 3D stereoscopic signal formats
- 4K – 4096x2160/24 video resolution support for commercial applications such as Digital Movie Theaters, CAD, Post Production, Graphics and etc.

Specifications



Technical:

- Input (Each): 1 HDMI; 1 wired IR on 3.5 mm stereo jack connector per slot
- Output (Each): 1 HDMI; 2 CAT5e/6 on RJ45 connectors;
- Control: Front panel push buttons and LED's; IR sensor front/rear; RS-232 Tx/Rx lines with full bi-directional operation
- Video/Audio Matrix Switching: Full matrix switching for HDMI Video matrix
- Wired IR Control Matrix: Each input/output section wired IR and unit wired IR can be switched into matrix in uni-directional operation to any of the inputs/outputs
- Link and Range: 1080p/60, 1920x1200 max. up to 75 ft. 1080i/60, 720p, 1080p/24 up to 100 ft.
- Deep Color Support: Digital video formats in Deep Color Mode at up to 12 bits/color
- HDMI® and HDCP Licensing: Fully licensed and compatible with all HDMI and HDCP technologies
- EDID Control: Each input EDID is either a choice of any of the active zone displays connected via HDMI or CAT5e/6 to the outputs or from internal library of 9 default EDID's
- DDC Communication: EDID and HDCP Bi-directional Transparency from Display to Source

General

- Regulation: CE, FCC, RoHS, WEEE
- Rack Mount: 1U
- KD-4x4XC Power: External Power Supply - 12V/2A
- Accessories: IR Remote Control, (4) KD-PS5V2A UL Certified Power Supply - 12V / 2A
- KD-4x4XC Product Dimensions: 17.125" W x 5.50" D x 1.75" H
- KD-CATHD4x4Rx Product Dimensions: 3.25" W x 1.875" D x .875" H
- KD-4x4XC Product Weight: 4.05 lb.
- KD-CATHD4x4Rx Product Weight: .25 lb
- Shipping Weight: 10 lb
- Enclosure: Black Metal

System Design Example

*To connect DVI, use HDMI to DVI adapters. HDMI is a registered trademark of HDMI Licensing, LLC & HDMI.org