

Specifications

Technical:

- » **Inputs/Outputs:** 1 HDMI connector, 1 stereo analog balanced or unbalanced audio 1VRMS/10K Ω on a Phoenix connector; 1 digital S/PDIF audio 0.5Vpp/75 Ω on an RCA connector, RS-232 Tx, Rx line and ground on Phoenix connector; wired IR bi-directional on Phoenix connector; 1 CAT6 Input on a shielded RJ-45 connector (for video/audio/data)
- » **Bandwidth:** TMDS bandwidth 10.2 Gb/s
- » **EQ Adjustments:** Precise Auto Adjust, Distance Measurement
- » **HDMI® and HDCP Licensing:** Fully licensed and compatible with all HDMI and HDCP technologies
- » **Link and Range:** 1080i/60, 720p, 1080p/24 UTP up to 250 ft. CAT6 UTP up to 280 ft.
- » **Deep Color Support:** Supports Digital Video Formats in Deep Color Mode at up to 12 bits/color
- » **Additional Non-HDMI Audio:** Left and Right Balanced or unbalanced on Phoenix connector or Coaxial Digital Audio S/PDIF on RCA connector
- » **DDC Signal (Data):** Input DDC Signal: 5 Volts p-p (TTL)
- » **HDMI Video/Audio Signal:** Input Video Signal: 1.2 Volts p-p
- » **HDMI Connector:** Type A, 19 Pin Female
- » **RJ45 Connector:** Shielded Link Connector RJ45
- » **DDC Communication:** EDID and HDCP Transparency from Display to Source
- » **Additional Non-HDMI Wired RS-232:** RS-232 Tx and Rx Line active and bi-directional up to 115,200 baud rate
- » **Additional Non-HDMI Wired IR:** IR line, active and bi-directional 0-5V TTL or -10 – 10V
- » **Power:** External UL Certified Power Supply – 5V DC / 2A, 110-240 VAC, 50-60 Hz

General

- » **Regulation:** CE, RoHS, WEEE
- » **Enclosure:** Black Metal
- » **Accessories:** Mounting Clip, HDMI Cable Clip
- » **Product Dimensions:** L = 2.75" W = 2.5" H = 1.5"
- » **Shipping Carton Dimensions:** L = 4.75" W = 8" H = 3"



- » **Product Weight:** 0.6 lb
- » **Shipping Weight:** 1.5 lbs