

Specifications

Technical:

- » Inputs/Outputs: 1 VGA/UXGA on an HD15 female connector 1Vpp/75 Ω or 1 Component (YPrPb) on VGA female to 3 RCA female breakout cable (included); 1 stereo analog balanced or unbalanced audio 1VRMS/10K Ω on a 3.5mm stereo female or male connector; 1 CAT5 Input on a shielded RJ-45 connector (for video/audio)
- » Resolution: Up to UXGA; 1080p
- » Equalization and Gain Adjustment: Manual adjustment by two potentiometers (Gain, EQ) for CAT5e/6 cable length measurement up to 1,000 ft.
- » K-Factor: 0.22 % @ optimal EQ
- » Video Isolation (Crosstalk): -45 dB @ 5 MHz
- » Analog Audio Max Input/Output Level: 4dBu on AC coupling (input); 4dBu on DC coupling (output)
- » Audio Bandwidth: 20Hz to 20kHz, @ 0dBu
- » Analog Audio Sample Rate Conversion: 48kHz
- » Resolution Conversion: 24 bits
- » Power: External Power Supply – 5V DC / 1A

General

- » Regulation: CE, RoHS, WEEE
- » Rack Mount: Bracket (included)
- » Enclosure: Molded ABS
- » Product Dimensions: 2" x 2.57" x 1"
- » Shipping Dimensions (KD-CATCVA): 10.5" x 7.75" x 2.5"
- » Shipping Dimensions (KD-CVARX): 10.25" x 6.5" x 2.5"
- » Product Weight: 0.5 lbs
- » Shipping Weight (KD-CATCVA): 2 lbs
- » Shipping Weight (KD-CVARX): 1 lb
- » Accessories: VGA to Component Breakout Cable, Stereo Cable, Mounting Bracket, UL Certified External Power Supplies