Specifications

Technical:

- » Inputs: 4/3/2 HDMI connectors
- Outputs: 1 HDMI connector
 Bandwidth: 10.2 Gb/s TMDS bandwidth
- » Link: Single Link: 1080p/60, 12 bit color depth, 1920x1200 max.
- » DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- » HDMI® and HDCP Licensing: Fully licensed and compatible with all HDMI and HDCP techologies
- » HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- » HDMI Connector: Type A, 19 Pin Female
- » DDC Communication: EDID and HDCP Bi-directional Transparency from Display to Source
- » EDID Control: Any of the active outputs connected via HDMI, or from an internal library of 6 default EDID settings.
- » Power Source: 5 Volt DC @ 2 Amps, 100-240 VAC, 50-60 Hz

- Degulation, CE DallC WEE

General

- » Regulation: CE, RoHS, WEEE
- » Rack Mount: 1U Rack Ears Included
- » Enclosure: Black Metal
- » Product Dimensions: L = 8.5" W = 4" H = 1.75"
- » Shipping Carton Dimensions: L = 15.5" W = 8.5" H = 3.75"
- » Product Weight: 1.5 lbs
- » Shipping Weight: 4.2 lbs
- » Accessories: Rack Ears, UL Certified Power Supply