

Specifications

Technical:

- » Inputs (8): RGsB or YPrPb on 3 RCA female 1Vpp/75 Ω
- » Outputs (8): RGsB or YPrPb on 3 RCA female 1Vpp/75 Ω
- » Max Video Input Level: VGA or YPrPb: 1.2Vpp on 75 Ω , AC coupling
- » Return Loss: -19dB
- » Max Video Output Level: VGA or YPrPb: 1.5Vpp on 75 Ω , DC coupling
- » Resolution: Up to UXGA; 1080p
- » Control: Front panel push buttons and LED's, front and rear Infrared Receiver, Wired IR on rear, RS-232 on Tx and Rx lines
- » Matrix Switching: Full matrix switching for Video
- » Video S/N Ratio: 58 dB RMS un-weighted; 65 dB RMS @5MHz weighted, optimal EQ
- » K-Factor: 0.22 % @ optimal EQ
- » Video Isolation (Crosstalk): -45dB @ 5MHz
- » Resolution Conversion: 24 bits
- » Power: +6V, 6.6A

General

- | | |
|---|--------------------------|
| » Regulation: CE, RoHS, WEEE | » Product Weight: 6 lb |
| » Enclosure: Black Metal | » Shipping Weight: 9 lbs |
| » Product Dimensions: L = 17.5" W = 7" H = 1.75" | |
| » Shipping Carton Dimensions: L = 23.5" W = 11" H = 4.5" | |
| » Accessories: IR Remote Control, UL Certified Power Supply | |