



Armored WDR Color EGG Dome Camera

- Powerful WDR (Wide Dynamic Range) Performance
- 550TVL Horizontal Resolution
- True Day & Night (ICR) W/ Built-in 22 Units IR LEDs
- Vari-Focal Lens (f2.6 ~ 11.0mm)
- Vandal-Proof & Weather-Proof (IP66)
- DSS Low Light Technology
- Privacy Masking / Motion Detection / Mirror
- Multi-Language OSD Menu
- Monitor Output Terminal for Easy Servicing
- 3-Axis Gimbal Bracket
- Supports DC 12V / AC 24V Power Supply

Key Features

- Sony 1/3" Vertical Double-Density Interline CCD
- Powerful WDR (Wide Dynamic Range) Performance
- 550TVL Horizontal Resolution
- Vandal-Proof & Weather-Proof (IP66)
- True Day & Night (ICR) W Built-in 22 IR LEDs
- Vari-Focal Lens (f2.6 ~ 11.0mm)
- Intensified DSS accumulation field number up to 500x
- On Screen Display (OSD) Menu
(OSD Languages: English, Spanish, German, Russian, Chinese)
- Privacy Masking / Motion Detection / Mirror
- Adjustable Contrast & Sharpness
- Advanced Back Light Compensation (BLC)
- Automatic Gain Control (AGC)
- Automatic White Balance (AWB)
- Fast Shutter Speed (1/60 ~ 1/100,000 sec)
- Monitor Output Terminal for Easy Servicing
- 3-Axis Gimbal Bracket
- Surface Mounting Bracket Included
- Cooling Fan and Heater for High/Low Temperature Environment
- Supports DC 12V / AC 24V Power Supply
- Wall-Mount Bracket Available (Sold Separately)



WDR (Wide Dynamic Range)

To Get Detail Information from Dark and Bright combination Image Without Any saturation, The WDR Technology is required. It combines bright areas with high shutter speed Exposure and Dark areas with low shutter speed exposure into one composite image




True Day & Night with ICR Mechanism

With the built-in dual filter system combination, this camera provides true color image at day time and real B/W image at night time. The removable IR Cut Filter is on to give true color image and off to increase the light sensitivity in day/night mode.

3-Axis Rotating Mechanism

This camera is mounted on a 3-axis rotating platform, which allows an installer to easily adjust the field of view horizontally, vertically, and/or with a rotary movement. With this feature, you don't need to worry about where the camera is attached and/or how it is oriented.



* Specifications & Features are subject to change without prior notice.

Within USA & Canada (Toll Free):

- Tel: 877-537-0118

- Fax: 877-537-0116

For Oversea Customers:

- Tel: 201-393-0118

- Fax: 201-393-0116

KT&C America, Inc.:

777 Terrace Ave. Suite 402, Hasbrouck Heights, NJ 07604

Email: sales-america@ktnccamerica.com

Part No.: KPC-VNW100NHV15

DSS Low Light Technology

Digital Slow Shutter (DSS) is a technology that enhances the low light performance of a camera, producing outstanding images in low light conditions, DSS slow the picture frame rate and increase the cameras sensitivity



Vandal-Proof Dome Housing

The die-casting aluminum dome housing and polycarbonate dome cover ensures the perfect camera durability and protects the camera from external shock.



IP66 Rating (Weather-Proof)

Meeting the standards of IP66, this dome will withstand dust and heavy seas. Rugged enough for any outdoor environment, yet cosmetically designed to fit in indoor environments.



Convenient OSD Menu


Camera settings can be easily controlled or adjusted by using the built-in joystick to access the integrated On-Screen Display (OSD) menu. Multiple language options are available: English, Spanish, German, Russian, Chinese

Secondary Monitor Output Terminal

The built-in secondary monitor output terminal gives the convenience of on-the-spot adjustments of the angle and focus.

0 Lux Min. Illumination with 22 IR LEDs

The KPC-VNW100NHV15 is equipped with Built-in High performance 22 units of IR LEDS that make the detected dark object extremely bright visual image in total darkness without any light. This camera can cover the reliable Video surveillance up to 100 Feet Long Distance




Wall-Mount Bracket Option Available


This rugged wall mount is built using a heavy duty die-cast aluminum body with a 1" NPT thread to support all our vandal domes. Attractively designed to install in any application. Bracket is sold separately.



KA-WM100



General Feature Diagram



* Specifications & Features are subject to change without prior notice.

Within USA & Canada (Toll Free):

- Tel: 877-537-0118

- Fax: 877-537-0116

For Oversea Customers:

- Tel: 201-393-0118

- Fax: 201-393-0116

KT&C America, Inc.:

777 Terrace Ave. Suite 402, Hasbrouck Heights, NJ 07604

Email: sales-america@ktnccamerica.com

Part No.: KPC-VNW100NHV15

Technical Specification

Model		KPC-VNW100NHV15	KPC-VNW100PHV15
Signal System		NTSC	PAL
Image Sensor		1/3" Sony Vertical Double –Density Interline CCD	
Scanning System		2:1 Interlace	
Scanning Frequency (H)		15.734 KHz	15.625 KHz
Scanning Frequency (V)		59.94 Hz	50 Hz
Total Pixels		811(H) x 508(V)	795(H) x 596(V)
Effective Pixels		768(H) x 494(V)	752(H) x 582(V)
Synchronization		Internal	
Horizontal Resolution		More than 550 TV Lines	
Lens Size		f2.6mm ~ 11.0mm Vari-Focal Lens	
S/N		More than 48dB (AGC Off)	
Min. Illumination		0 Lux (IR LED On)	
IR LED		22 IR LEDs, 850nm (IR Wavelength), $\pm 22^\circ$ (IR Half Angle), Up to 100Ft (IR Distance)	
Shutter Speed		1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
Video Output Level		1Vp-p Composite (75 Ω), Unbalanced	
Function	On-Screen Display (OSD)	Built-in	
	WDR	Off / On / Auto (Level Adjustment)	
	Digital Zoom Ratio	1.0x / 1.5x / 2.0x / 2.5x (WDR Off Mode)	
	Digital Slow Shutter	1-500 Field	
	Back Light Compensation (BLC)	On / Off (BLC Area & Ratio Adjustable)	
	Auto Gain Control (AGC)	Low / Mid / High	
	White Balance	ATW/ Push / Push Lock / User (R Gain, B Gain)	
	Privacy Masking	On / Off (8 Zone)	
	Mirror	On / Off	
	Motion Detection	On / Off (Zone, Level Adjustable)	
	Language Option	English / Spanish / German / Russian / Chinese	
Day & Night		True Day & Night (ICR)	
IP Rating		IP66 (Weatherproof)	
Gamma		$\gamma = 0.45$	
Operating Temperature		-10 °C ~ 50 °C (14 °F ~ 122 °F)	
Storage Temperature		-20 °C ~ 60 °C (-4 °F ~ 140 °F)	
Humidity		Less than 80%RH	
Power Supply		DC12($\pm 10\%$), Max 870mA / AC24($\pm 10\%$), Max 15.4W	
Dimensions	With Surface Mount	Dome ($\phi 100$ mm), $\phi 156 \times 151.5$ mm (H) : Dome ($\phi 3.937$ "), 5.906"(ϕ) x 5.964"(H)	
	Without Surface Mount	Dome ($\phi 100$ mm), $\phi 143 \times 126.0$ mm (H) : Dome ($\phi 3.937$ "), 5.630"(ϕ) x 4.960"(H)	

* Specifications & Features are subject to change without prior notice.

Within USA & Canada (Toll Free):

- Tel: 877-537-0118

- Fax: 877-537-0116

For Oversea Customers:

- Tel: 201-393-0118

- Fax: 201-393-0116

KT&C America, Inc.:

777 Terrace Ave. Suite 402, Hasbrouck Heights, NJ 07604

Email: sales-america@ktnccamerica.com