

LCD MONITOR FOR CCTV

22 Inch LCD

Model No. : L2200SCBK

- 1680X1050 @60Hz Resolution
- Ultra Slim Bezel
- Response Time 5ms
- Contrast Ratio 1000:1
- Brightness 300cd/m²
- RGB Analog & DVI-D
- BNC In/Out & RCA (Audio R/L)
- Component
- Built-in Speaker
- 3D-Comb, De-Interlace, PIP



DEVICE COLOR		Black
LCD	SIZE	22-inch diagonal
	PIXEL PITCH	0.282 x 0.282mm
	VIEWING ANGLE	±80° (Right/Left), 80° (Up), 80° (Down)
	CONTRAST RATIO	1000:1 (typ)
	COLOR DEPTH	16.7M Colors
	RESPONSE TIME(Tr+Tf)	5ms
	BRIGHTNESS	300cd/m2 (typ)
SCANNING FREQUENCY	HORIZONTAL	30 ~ 80KHz
	VERTICAL	56 ~ 75Hz
	RECOMMEND RESOLUTION	1680 x 1050 @60Hz
SPEAKER POWER		2 x 2 Watt
SPEAKERS		Built-in
SOUND FEATURES		Stereo R,L
INPUT CONNECTIONS	PC	H/V Separate TTL Level, RGB Analog (D-Sub 15pinX1)/Stereo Audio in (3.5dX1)
	COMPONENT	Yes
	DVI-D	Yes
	AV	Stereo Audio R,L (RCA X 2), CVBS (BNC X 1)
OUTPUT CONNECTIONS		Ear-phone (Stereo 3.5pi X 1), Pass through CVBS (BNC X 1)
POWER VOLTAGE		DC Adaptor 12V 3.33A
POWER CONSUMPTION(Max/DPMS)		< 40W/2W
SPECIAL FEATURES		3D-Comb Filter, De-Interlace, PIP
REMOTE CONTROL		Optional
DIMENSION	W x D x H	21.80 x 7.30 x 18.20 Inch
WEIGHT	NET / GROSS	14.30 Lb / 18.73 Lb
REGULATION	SAFETY	UL, FCC, CE