

# 10.4" Color HD LCD Monitor

LCD-1048HD

LCD-1048HDL

LCD-1048HDLX



LCD-1048HDL



LCD-1048HD



LCD-1048HDLX

- HD Compatible (supports 480p/i, 720p, 1080p/i)
- RS-232 serial control provided
- Composite video BNC IN/OUT capability
- Underscan capability
- On-screen display controls, with front controls for Power, Select, Menu, and Volume Up/Down
- Wireless remote control with hot key allows easy toggling between sources
- Rear IR jack allows direct connection for use with IR repeater systems
- Speaker output on board allows screw down connection for R/L audio
- Built-in amplifier provides ample power to drive right and left stereo 8 ohm speakers
- 2 built-in speakers
- LCD-1048HDL and LCD-1048HDLX are made of durable metal with black powder coating
- LCD-1048HD cabinet is made of durable ABS plastic with 2 key hole slots for wall mounting
- Built-in interface and proper cable exiting for wall arm mounting, VESA 75mm compliant
- Screw down DC feature provides additional security for power connection
- Response time: 15/25 ms (rising/falling)
- SPS included, 100~240 VAC

## Flush-mounted 10.4" Monitor Model LCD-1048HDL (shown above)

## Flush-mounted 10.4" Monitor with No Front Controls Model LCD-1048HDLX (shown above)

Dimensions(WHD): 337 x 247x 42mm / 13.3" x 9.7" x 1.7"

Installers Cut-Out (WH): 299 x 209mm / 11.8" x 8.2"

## Optional Accessories

DC-1500	Factory approved car cord
HM-400	Under-cabinet hinge mount
WM-31	Wall mount bracket (fixed)
WM-302	Wall mount with swing arm & 4-way adjustable

Display: 10.4" TFT LCD active matrix  
Back Light: 2 x CCFT  
Input Signal: [Composite, component, & S-Video, NTSC/PAL auto sensing]  
analog RGB

Dot Pitch: 0.206 (H) x 0.206 (V)mm  
Resolution: 1024(H) x 768(V) [700 lines for CCTV]  
Number of Pixels: 786,432 dots  
Brightness Rating: 350 cd/m<sup>2</sup> (Nit)  
Colors: 262,144  
Contrast Ratio: 500:1  
Viewing Angle L/R/T/B: 90/90/90/90 degrees  
Pixel Configuration: RGB Vertical Stripe  
Audio output: 5W x 2, 8 ohm

LCD-1048HD Dimension w/o desk stand (WHD): 269 x 229 x 47mm / 10.6" x 9.0" x 1.9"  
LCD-1048HD Dimension with desk stand (WHD): 269 x 229 x 152mm / 10.6" x 9.0" x 6.0"  
LCD-1048HDL / HDLX: Dimensions (WHD): 337 x 247x 42mm / 13.3" x 9.7" x 1.7"  
Actual visible screen size (WH): 210 x 158mm / 8.3" x 6.2"

Operating temperature: 50~104°F or 10~40°C  
Storage temperature: 14 ~ 158°F or -10 ~ 70°C

Power requirement/consumption: 12VDC, 2A, negative ground /24W  
Rear Terminal Connections: Composite: BNC IN/OUT jacks, 2 RCA IN jacks  
Component: 3 RCA IN jacks  
S-Video IN jack  
Audio: 3.5 PC audio IN, RCA L/R audio inputs,  
L/R screw down speaker connectors,  
and 3.5 audio line OUT

PC: 15-pin mini D-sub

RS-232: 9-pin

3.5 IR IN

Power: 2.1mm DC jack, screw down DC connector

LCD-1048HD Weight: Net: 1.2 kg. / 2.5 lbs.

Gross: 3.3 kg. / 7.3 lbs.

LCD-1048HDL / HDLX Weight: Net: 1.94 kg. / 4.28 lbs.

Gross: 3.4 kg. / 7.4 lbs.



Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

P.18

©2009 ToteVision

30K

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109  
Tel: 206-623-6000 • FAX: 206- 623-6609

E-mail: sales@totevision.com  
http://www.totevision.com

