

LCD-1560HDL - Front



LCD-1560HDL - Back



LCD-1560HDL Flush Mount Monitor

This high-definition, mid-size monitor is ideal for any commercial video use. It has the same features as the LCD-1901HD in a smaller screen size.

Benefits

- Displays HD signals (1080p/i and 720p)
- Widescreen (16:9) native aspect ratio
- Durable black steel case
- Built-in speakers
- Under scan capability
- IR remote control and also external IR jack
- RS-232 control
- Blue gun color calibration feature
- Composite BNC in/out for looping

Accessories

Related Products

- LCD-1560HD
- LCD-1560HDR

Specifications	
Mount	Flush
HD Compatible	Yes
Anti Glare Coating	Yes
Selected Color Temp.	No
Case	Metal
Built-in Power Supply	No
IR Remote Control	Yes
180° Rotation Display	No
Native Aspect Ratio	16:9
Visible Screen Size (WH)	344.2 x 193.5mm / 13.6" x 7.1"
Resolution	1366(H) x 768(V) dots
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	500:1
Back Light	CCFT (50 K)
PC Compatibility	Yes
Dot Pitch	0.252(H) x 0.252(V)mm
Colors	8-bit, 16.2M
Number of Pixels	1,049,088
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 ohm, 2 W, 28 x 40mm oval type x 2
Viewing Angle (L/R/T/B)	90/90/65/65 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/ Deskstand	
Dimensions w/o Deskstand	419 x 290 x 51mm / 16.5" x 11.4" x 2.0"
Operating Temp/Humidity	6 ~ 104°F / -14 ~ 40°C
Power Requirements	Regulated 12VDC, 3A, negative ground Part No. DC-1500 required for use in vehicles
Power Consumption	12W (max)
Component	RCA YPbPr jacks
Composite	RCA video IN/OUT jacks
S-Video	IN jack
PC	15-pin mini D-sub
HDMI / DVI / RS-232	Yes / No / 9-pin
Audio	2 RCA R/L audio inputs, PC audio IN, and RCA audio R/L intputs
Power	DC IN
Weight	Net 3.2 kg / 7.1 lbs Gross 7.35 kg / 10.7 lbs
Installers Cut Out	14 7/8" x 10 3/8"
GSA	Yes