

23" Free-standing HD LCD Monitor

LCD-2300HD



- HD compatible (supports 480p/i, 720p, 1080i)
- PIP: Picture in picture capability
- 2 built-in speakers provide 3D MTS stereo
- Hard anti-glare coating enhances viewing
- Composite, S-Video, component, DVI, PC, HDMI
- Black case made of durable ABS plastic
- Wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Built-in power supply 100-240VAC, 50/60 Hz
- Closed-caption and V-chip features
- IR remote control works within 30 feet
- RS-232 serial port control
- Widescreen 16:9 aspect ratio, 4:3, zoom
- 3D-comb filter
- Environmentally safe: RoHS compliant, no x-radiation, power-saving feature

Resolution: 1366 (H) x 768 (V) dots
Brightness rating: 500 cd/m² (Nit)
Contrast Ratio: 400:1

Display: 23.0" TFT LCD active matrix

Back Light: Built-in (12 CCFT)

Input Signal: Composite NTSC/PAL, S-Video
 component, analog RGB, HDMI, DVI
 Has digital RGB

PC compatibility: IBM compatible

Dot Pitch: 0.39(V) x 0.39(H)mm

Colors: 16.7M

Contrast Ratio: 400:1

Number of Pixels: 983,040

Response Time: 15/10ms

Audio output: 10W x 2

Speakers: 10W + 10W

Viewing angle L/R/T/B: 85/85/85/85 degrees

Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Dimensions (WHD): 720 x 475 x 240mm / 28.3" x 18.7" x 9.4"

Dimensions w/o deskstand (WHD): 720 x 413 x 81mm / 28.3" x 16.3" x 3.2"

Actual visible screen size (WH): 499 x 299mm / 19.6" x 11.8"

Operating temperature/humidity: 50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity

Power Requirements: 100~240VAC / 50~60 Hz

Power Consumption: 120 W (max)

Rear Terminal Connections: 2 composite RCA Video IN

Component: RCA YPbPr & R/L audio inputs, and
 RCA Y/Cb/Cr & R/L audio inputs

2 S-Video IN

Audio: 2 RCA R/L audio inputs, PC audio IN, and
 RCA audio R/L outputs

PC: RGB 15-pin D-sub

HDMI, DVI, RS-232: 9-pin

Power: AC IN

Weight: Net: 11.58 kg. / 25.5 lbs.

Gross: 14.56 kg. / 32.8 lbs.

Optional Accessories

PLT-2300	VESA conversion plate (for landscape & portrait positioning)
WM-3018VT	Fixed wall mount bracket
WM-4200VT	4-way pan/tilt wall mount bracket (order w/ PLT-2300)
WMC-2342	Ceiling mount (order w/ PLT-2300)