

LCD-411 with BNC



LCD-410 with Audio



Right Side



Left Side

**MODEL NUMBERS**

LCD-411

LCD-410 (with audio; BNC IN Cable)

DESCRIPTION

LCD-411 Only: BNC IN/OUT jacks located on top for easy access (with self-termination feature)

LED backlight provides longer life, uses less power and provides better color saturation

Battery pack for field monitor use included

Ideal for troubleshooting system setup/fault location

Switch for Auto/Manual color adjustment

Low power consumption

Case made of durable ABS plastic

Manual controls for tint, color, brightness (and audio volume for LCD-410)

Battery pack provides approximately 5 ~ 6 hrs operation

Snap-on battery pack holds 8AA or 9 NiCad rechargeable batteries (batteries not included)

Response Time: 30ns/50ns (Rising/Falling)

LCD-411KIT 4" Field Kit with BNC IN/Cable with clip-on battery pack, tote bag, and AC adaptor

LCD-410KIT 4" Field Kit with Audio (no BNC IN/OUT) with clip-on battery pack, tote bag, and AC adaptor

For Rechargeable Battery Pack order part # BP-563 to go in TB-410 tote bag

OPTIONAL ACCESSORIES

AC-1000 AC adaptor

BP-563 Rechargeable 2200mh NiCad battery pack
Provides approximately 6 hrs. operation.

DC-12 Car cord

DC-12D Dual car cord

HS-1 Hot Shoe mount

MB-1 Desk Stand

MB-72M Metal Mounting Bracket

TB-410 Custom Totebag with sun shield

WM-1 Wall mount bracket

SPECIFICATIONS

Resolution 383(H) x 234(V) dots

Brightness Rating 300 cd/m² (Nit)

Dot Pitch 0.214(H) x 0.234(V)

Contrast Ratio 150:1

Display 4" TFT LCD active matrix

Back Light LED

Input Signal NTSC/PAL

Operating Power Range 10 ~ 30 VDC

Viewing Angle (L/R/T/B) 45/45/30/10

Dimensions w/pack (WHD) 145 x 117 x 58mm / 5.7" x 4.6" x 2.3"

Dimensions w/o pack (WHD) 145 x 117 x 45mm / 5.7" x 4.6" x 1.8"

Monitor Mounting Mounting pad with ¼ - 20 threaded socket

Actual Visible Screen size (WH) 82.1 x 61.8mm / 3.2" x 2.4"

Operating Temperature 50 ~ 104°F or 10 ~ 40°C

Storage Temperature -13 ~ 140°F or -25 ~ 60°C.

Power Requirement / Consumption 12VDC, 380mA, + pin / 5 W

Connections **LCD-411** BNC video IN/OUT (female) jacks
2.1mm DC IN jack
LCD-410 3.5mm A/V IN/OUT jacks with cables,
2.1mm DC IN jack with cable

Weight **Net** 425g / 15oz **Gross** 0.61 kg / 1.35 lbs