

LCD-800D Dual Monitors in 19" Rack Mount Kit



LCD-801


LCD-801 Shown
with MB-2 Desk Stand


MODEL NUMBERS

LCD-800D Dual Monitors in Rack Mount Kit

LCD-801

DESCRIPTION

S-Video capability

Mirror and upside down image picture control

Anti-glare coating provides enhanced display

Remote control for maximum convenience

LCD-801: Key lock feature allows front control buttons to be disabled
Instant-On capability when power is applied
Power saving ON/OFF feature

OPTIONAL ACCESSORIES (LCD 801)

BP-563 Rechargeable battery pack 2200mAH NiCad
battery pack (provides approximately 5 hrs. operation)

SPECIFICATIONS

Resolution	1440(H) x 468(V) dots
Brightness Rating	350 cd/m ² (Nit)
Dot Pitch	0.112(H) x 0.252(V)mm
Contrast Ratio	350:1
Display	8" (diagonal) TFT LCD active matrix
Back Light	2 CCFT
Input Signal	NTSC/PAL
Colors	262,144
Color Configuration	Stripe
Number of Pixels	673,920 Dots
Pixel Configuration	RGB Vertical Stripe
Video Input Level	1.0 V P-P (positive) 75 Ohm
Viewing angle (L/R/T/B)	50/50/15/35
Actual screen size (WH)	161.28 x 117.94mm / 6.3" x 4.6"
LCD-801 Dimensions (WHD)	209 x 159 x 32mm / 8.2" x 6.3" x 1.3"
LCD-800D Dimensions (WHD)	Occupies 4 RU (7") x 1.5"
Operating temperature	50 ~ 104°F or 10 ~ 40°C / 85% RH (max)
Storage temperature	-25 ~ 140°F or -32 ~ 60°C
LCD-801 Power Requirements	12 ~ 24VDC, 2000mA, + pin
LCD-800 Power Requirements	12 ~ 24VDC, 1A, + pin
LCD-801 Power Consumption	10 W (max)
LCD-800 Power Consumption	15 W (max)
Connections	LCD-801 Cable w/ RCA video IN, 2.1mm DC IN jack, and cable w/ S-Video jack LCD-800D Mini DIN cable w/ RCA video IN, BNC video IN/OUT, S-Video 2.1 DC IN jacks
LCD-801 Weight	Net 650g 22.8 oz Gross 2.3 kg / 5 lbs
LCD-800D Weight	Net 3.2 kg / 7lbs Gross 4.4 kg / 9.7 lbs