

Cost-Effective High Resolution, Security Surveillance TFT Color LCD Monitors



LCM-1501 15"

LCM-1701 17"

LCM-1901 19"

Features

- Three Screen Sizes (15", 17" and 19") available
- High Resolution Image 550TVL
- Composite 1& 2-NTSC/PAL(BNC), S-Video(Y/C) and Analog VGA(D-Sub)
- 16.2 Million Colors
- Loop-through Composite Video
- Fast Response Time (16msec/15", 8msec/17" & 19")
- Two Audio Speakers
- Power AC 100V ~ 240V (No AC adaptor required)
- All Safety Standards (FCC, UL, cUL)

LCM Series High Resolution Security Surveillance Color LCD Monitors

Specifications

		LCM-1501	LCM-1701	LCM-1901
Panel:	Type:	Amorphous Active Matrix Super TFT LCD		
	Viewable size:	15" (TN) diagonal	17" (TN) diagonal	19" (TN) diagonal
	Pixel pitch:	0.297mm x 0.297mm	0.264mm x 0.264mm	0.294mm x 0.294mm
	Number of pixels:	1024 x 768	1280 x 1024	1280 x 1024
	Display colors:	16 Million Colors		
	Brightness:	450cd/m2	300cd/m2	300cd/m2
	Contrast ratio:	400:1	500:1	700:1
	Response time:	16msec.	8msec.	8msec.
	Viewing angle(L/R):	65/65	75/75	75/75
	Viewing angle(U/D):	45/55	75/60	75/60
Frequency:	Horizontal:	30 ~ 60KHz		
	Vertical:	56 ~ 75Hz		
3Line comb filter:		Built-in		
Resolution:	Horizontal:	550TVL		
Overscan controls:	0%/5%/10%:	Built-in		
Multimedia:	Sound:	RCA Jack type, 500mVrms, 10K ohms		
Display area:	Max. (W X H):	12.0" x 9.0"	13.3" x 10.6"	14.8" x 11.9"
Front controls:		OSD (Color Temp, Contrast, Brightness, Color, Sharpness, Tint)		
Power:	Embedded DC adaptor:	AC 100 ~ 264V, 50/60Hz		
Input signal:	Input:	RGB(15pin), composite (BNC) 1 & 2, S-Video (Mini-DIN), Audio (RCA)		
	Output:	Composite (BNC) 1 & 2		
Compatibility:	Analog RGB:	VGA, SVGA, XGA, SXGA		
	Video:	NTSC/PAL Standard		
Regulations:	EMI:	FCC Class A		
	Safety:	IEC60065(CB), CE, UL, cUL		
Wall mount:		VESA Standard 100mm x 100mm		
Dimensions (WxHxD):	Product:	14.4" x 15.3" x 7"	15.4" x 16.7" x 7"	16.9" x 17.7" x 8.7"
	Ship in:	17.5" x 18.3" x 9.2"	18.4" x 19.3" x 9.2"	20" x 20.6" x 10.7"
Weight:	Product:	12.3 lbs	13.2 lbs	15.4 lbs
	Ship in:	16.7 lbs	17.6 lbs	20.5 lbs
Power consumption:	Maximum:	31W	36W	40W
	DPMS:	Under 3W		
Accessories:	Standard:	Desktop stand		
	Option:	Tilt & Swivel Wall Mount (IK-LCD-75-100-B)		

Design and specifications are subject to change without notice.

Ikegami

IKEGAMI ELECTRONICS (U.S.A.), INC.

URL <http://www.ikegami.com>

**HEADQUARTERS
WESTCOAST OFFICE**

37 Brook Avenue, Maywood, NJ 07607 Phone (201)368-9171 Fax (201)569-1626
2631 Manhattan Beach Blvd., Redondo Beach, CA 90278
Phone (310)297-1900 Fax (310)536-9550

**SOUTHWEST OFFICE
MIDWEST OFFICE
SOUTHEAST OFFICE**

773 Bearden Road, Waxahachie, TX 75167 Phone (972)869-2363 Fax (972)556-1057
747 Church Road, Unit C1, Elmhurst, IL 60126 Phone (630)834-9774 Fax (630)834-8689
5200 N.W. 33rd Avenue, Suite 111, Fort Lauderdale, FL 33309
Phone (954)735-2203 Fax (954)735-2227