

LED-1002HD2 - Front



LED-1002HD2

Two 9.7" rack-mount monitors feature the latest screen imaging technology for enhance clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight for better color, longer-life, and lower power
- Wide viewing angle
- Excellent contrast range
- Very fast response time
- Image enhancing - 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

LED-1002HD2 - Back



Specifications	
Model	LED-1002HD2
Mount	Rack mount (5RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Selectable Color Temp.	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	197.6 x 148.8mm / 7.8" x 5.9"
Resolution	1024(H) x 768(V) dots
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Colors	262,144
Number of Pixels	786,432
Response Time	2ms/2ms (Rising/Falling)
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	RGB Vertical Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	3D interlace & DNR, 4H filter
Dimensions	479 x 221.4 x 47/18.9" x 8.72"x 1.85", 5RU
Operating Temp/Humidity	32 ~ 104°F or 0 ~ 40°C
Power Requirements	12VDC, 2A, negative ground
Power Consumption	30W (max)
Composite	BNC IN/OUT jacks x 2
PC	15-pin mini D-sub
HDMI	Yes
Audio	no
Power	2.1mm DC IN jack
Weight	Net 3.1 kg / 6.8 lbs/ Gross: 3.7 Kg / 8.2 lbs
GSA	Yes