42″ LED Monitor

LED-4200HDMT - Front

LED-4200HDMT - Back

LED-4200HDMT

This monitor is ideal for digital signage and public displays.

Benefits
True HD (1080p/i) with no downscaling
LED backlight – brighter picture using less power
Great picture quality - 10 Bit / 120Hz
Wide viewing angle (89/89/89/89)
ATSC / QAM Tuner
Widescreen (16:9) native aspect ratio
Built-in stereo speakers
Built-in removable desk stand
IR remote control
RS-232 control

Accessories
PLT-3742 VESA conversion plate for 100x100mm, 100x200mm, 200x200mm
WM-3742 Fixed wall mount bracket
WM- 4200VT 4 way pan/tilt wall mount bracket (order with PLT-3742)
WMC- 2342 Ceiling mount bracket (order with PLT 3742)

Related Products

Specifications	
Mount	Desk Stand
HD Compatible	Yes
Anti Glare Coating	Yes
Selected Color Temp.	Yes
Case	Durable ABS Plastic / Metal
Built-in Power Supply	Yes
IR Remote Control	Yes
180˚ Rotation Display	No
Native Aspect Ratio	16:9
Visible Screen Size (WH)	930 x 523mm / 36.6″ x 20.5″
Resolution	1920(H) x 1080(V) dots
Brightness Rating	450 cd/m²
Contrast Ratio	4000:1
Back Light	LED (60 K)
PC Compatibility	Yes
Dot Pitch	0.4845(H) x 0.4845(V) mm
Colors	16.7M
Number of Pixels	2,073,600
Response Time	6.5ms (Rising/Falling)
Audio Power / Speakers	8W x 2 / 8W + 8W
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/ Deskstand	1059 x 714 x 241 mm/41.7″ x 28.1″ x 9.3″
Dimensions w/o Deskstand	1059 x 650 x112mm/41.7″ x 25.6″ x 4.4″
Operating Temp/Humidity	32-122 F/ 0-50 C, 20% ~ 90% humidity
Power Requirements	90 ~ 240 VAC, 50/60 Hz
Power Consumption	230W (max)
Component	RCA YPbPr
Composite	RCA Video IN
RoHS Compliant	Yes
S-Video	IN Jack
PC	RGB 15-pin D-sub
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	RCA R/L audio inputs, PC audio IN, and RCA audio R/L outputs
Power	AC IN
Weight	**Net** 30.5 kg / 68 lbs **Gross** 35.8 kg / 79 lbs
GSA	Yes