

LED-5500HDT - Front



LED-5500HDT

55" LCD monitor with LED backlight is suitable for high definition viewing in public space areas, guest suites, and corporate board rooms.

Benefits

- LED backlight - brighter picture using less power
- Full HD display - 1080i/p with no downscaling
- Wide viewing angle
- Anti-glare surface treatment
- Widescreen native aspect ratio
- Built-in 10watt stereo speakers
- Built-in removable desk stand
- IR remote control
- RS-232 control
- Closed Caption
- Aspect Ratio Control

Accessories

WM- 3742 wall mount bracket (fixed)

Related Products

Specifications	
Mount	Desk stand:
HD Compatible	Yes
Anti Glare Coating	Yes
Selected Color Temp.	Yes
Case	ABS Durable Plastic
Built-in Power Supply	Yes
IR Remote Control	Yes
Tuner	ATSC/Clear QAM, PLL 181 Ch., CATV 125 Ch.
Native Aspect Ratio	16:9
Visible Screen Size (WH)	1209 x 680 mm / 47.6" x 26.8"
Resolution	1920 x 1080 (Full HD)
Brightness Rating	450
Contrast Ratio	4,000
Back Light	LED (50K)
PC Compatibility	Yes
Dot Pitch	0.21(H) x 0.63(V)mm
Colors	16.7 M
Number of Pixels	2,073,600
Response Time	5.5 ms (Rising/Falling)
Audio Power / Speakers	10W x 2, 8 Ohm
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/ Deskstand	1310 x 941.3 x 342 mm/ 51.8" x 37" x 13.5"
Dimensions w/o Deskstand	1310 x 892 x 118 mm/ 51.8" x 35.2" x 4.7"
Operating Temp/Humidity	32 ~ 122°F / 0 ~ 50°C
Power Requirements	100 ~ 240 VAC, 50/60Hz
Power Consumption	138 W
Component	RCA Y/Pb/Pr
Composite	RCA
RoHS Compliant	Yes
S-Video	IN jack
PC	RGB 15 Pin D-Sub
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	RCA L/R audio IN, 3.5 PC audio IN
Power	A/C IN
Weight	Net: 39.1 kg / 86 lbs Gross: 52.1 kg / 115 lbs

GSA

Yes