

Technical Data Sheet Access Control

2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

LS1822 **PART NUMBER:**

DESCRIPTION: Access Control Composite Cable: Card Reader Cable, REX Cable, Lock Power Cable, Door

Contact Cable. Lickity Split Design

NEC RATING: CM

(UL) C(UL) Listed **APPROVALS:**

APPLICATION: Indoor for: (Access Control)

Construction Parameters: Card Reader

Conductor 22 AWG Bare Copper

Stranding 7x30

PVC Thermoplastic Insulation Material Insulation Thickness PVC: 0.007" Nom.

Number of Conductors

Shield Overall Shield

Drain Yes **PVC** Jacket Material Jacket Thickness .017" Overall Cable Diameter 0.167" Nom.

Jacket Color Orange

Electrical Parameters: Card Reader

Nom. D.C.R. 17 ohms/1000ft 55pf/ft*, 99pf/ft** Nom. Capacitance pf/ft.

Capacitance between conductors

Capacitance between one conductor and the other to the shield

Construction Parameters: Door Contact

Conductor 22 AWG Bare Copper Stranding 7x30

Insulation Material

PVC Thermoplastic PVC: 0.007" Nom. **Insulation Thickness**

Number of Conductors Shield None Drain

None Jacket Material PVC Jacket Thickness .017" Overall Cable Diameter 0.120" Nom. Jacket Color White

Electrical Parameters: Door Contact

Nom. D.C.R. 17 ohms/1000ft **Construction Parameters: Request to Exit**

Conductor 22 AWG Bare Copper

Stranding 7

Insulation Material PVC Thermoplastic Insulation Thickness PVC: 0.010" Nom.

Number of Conductors 4
Shield None
Drain None
Jacket Material PVC
Jacket Thickness .015"
Overall Cable Diameter 0.138" Nom.

Jacket Color
Electrical Parameters: Request to Exit

Nom. D.C.R. 17 ohms/1000ft

Construction Parameters: Lock Power

Conductor 18 AWG Bare Copper

Blue

Gray

Stranding 7x26

Insulation Material PVC Thermoplastic Insulation Thickness PVC: 0.008" Nom.

Number of Conductors 4
Shield None
Drain None
Jacket Material PVC
Jacket Thickness .017"
Overall Cable Diameter 0.183" Nom.

Electrical Parameters: Lock Power

Nom. D.C.R. 6.2 ohms/1000ft

Overall Cable Assembly:

Jacket Color

Overall Cable Diameter .440"

All conductor Colors Black, Red, White, Green, Brown, Blue

Jacket Color Lickity Split Design

RoHS Compliant Yes

Specification Issue Date: 2/09 Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.

The information presented here is, to the best of our This document is the property of West Penn Wire.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all Proprietary and not to be reproduced by any means recommendations or suggestions are presented without written consent of West Penn Wire without guarantee or responsibility on our part. We

disclaim all liability in connection with the use of information contained herein or otherwise.