

M511E/M511W Day/Night Pan/Tilt IP Camera



- ▶ **Simultaneous MPEG-4 and Motion JPEG**
- ▶ **True day/night with automatic removable IR-cut filter**
- ▶ **Infrared LEDs with 10m effective range**
- ▶ **Power over Ethernet (M511E) or Wireless (M511W)**

- Progressive scan CMOS
- Simultaneous MPEG-4 and Motion JPEG
- 30 frames per second in all resolutions
- True day/night capabilities with automatic removable IR-cut filter
- 850nm infrared LEDs with 10m effective range
- Motorized wide-range pan and tilt
- 32 preset positions, 4 patrol sets
- Two-way audio and built-in microphone
- Power over Ethernet IEEE 802.3af (M511E)
- Wireless 802.11b/g (M511W)
- 1 x alarm input, 1 x alarm output
- SSL v3 advanced HTTPS encryption
- WEP, WPA, WPA2 advanced wireless security (M511W)
- 3GPP mobile surveillance
- Multi-lingual user interface
- 32 channel surveillance software

Technical Specifications

Models	M511E, M511W
Image sensor	1/4" Progressive scan CMOS sensor
Lens	F2.0, 4.3 mm
Angle of view	49° diagonal
Digital Zoom	10x digital
Min Illumination	0.5 Lux 0 Lux with IR LEDs on
IR working distance	10 M
IR LEDs	5 φ IR LEDs x 12 (850nm)
Day/Night function	Mechanical IR cut filter
Pan/Tilt	354° pan range, 60°/sec pan speed 125° tilt range, 80°/sec tilt speed
S/N Ratio	50dB
Video Compression	Motion JPEG MPEG-4 Part2 (ISO/IEC 14496-2), Profile: SP
Resolutions	Motion JPEG: 3 resolutions from 640x480 to 160x120 via API, 3 resolutions via configuration web page MPEG-4: 3 resolutions from 640x480 to 160x120 via API, 3 resolutions via configuration web page
Frame rate	Motion JPEG: Up to 15 fps at 640x480 (4:3 resolution) MPEG-4: Up to 30 fps at 640x480 (4:3 resolution)
Video streaming	Simultaneous Motion JPEG and MPEG-4 (Dual streaming) Controllable Frame rate and bandwidth Support Unicast and Multicast Support 3GPP/ISMA RTSP (Real Time Streaming Protocol)
Image settings	Rotation: Mirror, Flip, Mirror Flip brightness, contrast, saturation, hue Overlay capabilities: time, date, text and privacy image
Shutter time	1/7.5 ~ 1/120 sec.
Audio	Two-way (full duplex) External microphone input or line input Audio compression: G.711 PCM, 8kHz, 64 kbit/s
Wireless Encryption	IEEE 802.11b/g (M511W)
Security	Multiple user access levels with password protection, HTTPS encryption WEP 64/128 bit, WPA/WPA2-PSK
Users	5 simultaneous users Unlimited number of users using multicast
Alarm	Alarm input 5V/12V DC
Input/Output	Alarm output Max 30W

Alarm and event management	Input: alarm buffer, alarm input, motion detection Output: FTP, SMTP, HTTP event, alarm output Pre-and post alarm buffer (M511E)
Connectors	RJ-45 for Ethernet 10/100 Base-T DC power jack Terminal blocks for 1 alarm input, 1 output Reset push switch 3.5 mm jack for Mic/Line, 3.5 mm jack for line out
Casing	PC+ABS casing
Power	12V DC, 1A, Max 12W PoE (Power over Ethernet) Built-in IEEE 802.3af (M511E)
Operating conditions	0 ~ 50 °C (32 ~ 122 °F)
Installation, management, and maintenance	ZAVIO Camera Management tool on CD and web-based configuration. Configuration of backup and restore Firmware upgrades over HTTP, firmware available at www.zavio.com
Minimum web browsing requirement	Pentium 4 1.8GHz (or equivalent AMD) 64 MB RAM graphic cards (or equivalent on-board graphic cards) 512 MB RAM Windows 2000, 2003, XP or Vista Mac OS Leopard 10.5
Supported protocols	Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, RTCP, HTTP, TCP, UDP, 3GPP/ISMA RTSP
Included accessories	Quick Installation Guide, CD (ZAVIO CamGraba IP System, Intelligent IP Installer, User Manuals, and Language Pack), mounting and connector kits, power supply 12V DC
Video management software	ZAVIO CamGraba IP System software, for viewing, recording and archiving up to 32 cameras See http://www.zavio.com/support_softwares.php for more software application
Approvals	CE, FCC, RoHS
Dimensions (HxWxD) and weight	112 x 114 (φ)mm (4.4" x 4.4") 281 g (0.6 lb) excl. power supply



Physical Description

