

Technical Data Sheet- Category 5E Network Outdoor

WEST PENN WIRE

2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com



PART NUMBER:	M57561
DESCRIPTION:	24 AWG.- 4 PAIR Solid bare copper conductors, unshielded with an overall jacket.- Outdoor
NEC RATING:	--
APPROVALS:	--
APPLICATION:	Outdoor - Category 5E Applications- Ethernet, IP Cameras, Digital Integration Meets TIA/EIA 568B.2 Category 5e Specifications

Construction Parameters:

Conductor	24 AWG Bare Copper
Stranding	Solid
Number of Conductors	8 (4 Pair)
Insulation	Thermoplastic Polyolefin
Shield	None
Drain	None
Water blocking Polymer	Yes
Jacket Material	Polyethylene
Overall Cable Diameter	0.251" Nom.
Approximate Cable Weight	31 Lbs/1M' Nom.
Flame Rating	--

Electrical & Environmental Properties:

Operating Temperature Rating	-20°C To +60°C
Operating Voltage Rating	300 V RMS
DC Resistance per Conductor @ 20deg C	8.9 Ohms/100m Nom.
Mutual Capacitance	15 pf/ft Nominal
Nominal Impedance	100 Ohms+/-15% (1-100Mhz)
Velocity of Propagation	66% Nominal
Delay Skew	25ns/100m MAX
Standards	TIA/EIA568-B.2
Insulation Colors	1.Blue/White-Blue, 2. Orange/White-Orange 3. Green/White-Green, 4. Brown/White-Brown
Jacket Color	Black
RoHS Compliant	Yes

Electrical Specifications:

Frequency: MHz	1	10	25	100	200
Insertion Loss: dB/100m	1.8	5.8	9.3	19.6	28.8
NEXT: dB/100m	80	64	59	50	46
ACR: dB/100m	70.3	50.9	41.1	40.3	35.8
PS-NEXT: dB/100m	73	58	52	43	40
PS-ACR: dB/100m	66.3	46.9	37.1	17.3	3.3
ELFEXT: dB/100m	67.8	47.8	39.8	27.8	21.8
PS-ELFEXT: dB/100m	64.8	25	36.8	24.8	18.8
RL: dB	20	25	24.3	20.1	18

Mechanical Properties:

Max. Recommended Pull Tension

25 lbs.

Min. Bend Radius (Install)

4x cable OD- 1inch Min.

Accessories:

Connectors: Jacks

AX101310	Black
AX101315	Blue
AX101314	Green
AX101312	Red
AX101313	Yellow
AX101309	White
AX101311	Orange
AX101308	Ivory

Connectors: Plugs

32-EZP	Cat 5E EZ RJ45
--------	----------------

Tools:

TL-135	110 Punch down tool
TL-EZRJ45	EZ Crimp Tool

Cable Assemblies:

WP66xx-3	3ft- Replace xx- 70(Gray), 72(Blue), 74(Red)
WP66xx-7	7ft- Replace xx- 70(Gray), 72(Blue), 74(Red)
WP66xx-10	10ft- Replace xx- 70(Gray), 72(Blue), 74(Red)
WP66xx-15	15ft- Replace xx- 70(Gray), 72(Blue), 74(Red)
WP66xx-25	25ft- Replace xx- 70(Gray), 72(Blue), 74(Red)

Specification Issue Date: 4/09

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.